05/08/99

PROJECT: 17BP.14.R.68

CONTRACT: DN00181



VICINITY MAP

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

MACON COUNTY

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.14.R.68	1	

STATE PROJ. NO.	F. A. PROJ. NO.	DESCRIPTION
17BP.14.R.68		PE, R/W, UTIL
17BP.14.R.68		CONST.

LOCATION: BRIDGE 008 (OVER BERRY PRONG ELLIJAY CREEK) ON SR 1001 (ELLIJAY RD.)

TYPE OF WORK: GRADING, PAVING, DRAINAGE & STRUCTURE

See Sheet 1-A For Index of Sheets
See Sheet 1-B For Conventional Symbols



GRAPHIC SCALES

50 25 0 50 100
PLANS

50 25 0 50 100
PROFILE (HORIZONTAL)

10 5 0 10 20
PROFILE (VERTICAL)

DESIGN DATA

ADT (2008)= 520

V = 35 MPH

FUNC CLASS = LOCAL
SUB–REGIONAL TIER

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT 17BP.14.R.68	=	*0.0944 MI*
LENGTH STRUCTURE TIP PROJECT 17BP.14.R.68	=	*0.006 MI*
TOTAL LENGTH TIP PROJECT 17BP.14.R.68	=	*0.1004 MI*

NCDOT CONTACT: JOSHUA DEYTON, P.E.
PROJECT ENGINEER

Prepared In the Office of:
Mattern & Craig
CONSULTING ENGINEERS – SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 – FAX (828) 254-4562

2012 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE: AUGUST 1, 2013

LETTING DATE: MAY 13, 2014

JAMES B. VOSO, P.E.
PROJECT ENGINEER

DANA BOLDEN, P.E.
PROJECT DESIGN ENGINEER

HYDRAULICS ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 026945 ENGINEER DANA J. BOLDEN

SIGNATURE:

ROADWAY DESIGN ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. VOSO

SIGNATURE:

DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA

STATE OF NORTH CAROLINA • DEPARTMENT OF TRANSPORTATION •

P.E.
STATE HIGHWAY DESIGN ENGINEER

9:40:23 AM
N:\325\Bridge008\Roadway\Proj\17BP14R68_RDY_TSH.dgn
bgross

PROJECT REFERENCE NO.	SHEET NO.
17BP.14.R.68	1-A
ROADWAY DESIGN ENGINEER	PAVEMENT DESIGN ENGINEER

INDEX OF SHEETS – GENERAL NOTES – LIST OF STANDARDS

INDEX OF SHEETS

2012 ROADWAY ENGLISH STANDARD DRAWINGS

The following Roadway Standards as appear in "Roadway Standard Drawings" Highway Design Branch – N. C. Department of Transportation – Raleigh, N. C., Dated January, 2012 are applicable to this project and by reference hereby are considered a part of these plans:

STD.NO.	TITLE
DIVISION 2 – EARTHWORK	
200.02	Method of Clearing – Method II
225.02	Guide for Grading Subgrade – Secondary and Local
225.04	Method of Obtaining Superelevation – Two Lane Pavement
DIVISION 5 – SUBGRADE, BASES AND SHOULDERS	
560.01	Method of Shoulder Construction – High Side of Superelevated Curve – Method I
DIVISION 8 – INCIDENTALS	
862.01	Guardrail Placement
862.02	Guardrail Installation

GENERAL NOTES: 2012 SPECIFICATIONS

EFFECTIVE: 01–17–12
REVISED: 07/30/12

GRADE LINE:
GRADING AND SURFACING:

THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. GRADE LINES MAY BE ADJUSTED AT THEIR BEGINNING AND ENDING AND AT STRUCTURES AS DIRECTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE–IN.

CLEARING:

CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II.

SUPERELEVATION:

ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH STD. NO. 225.04 USING THE RATE OF SUPERELEVATION AND RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

SHOULDER CONSTRUCTION:

ASPHALT, EARTH, AND CONCRETE SHOULDER CONSTRUCTION ON THE HIGH SIDE OF SUPERELEVATED CURVES SHALL BE IN ACCORDANCE WITH STD. NO. 560.01.

SIDE ROADS:

THE CONTRACTOR WILL BE REQUIRED TO DO ALL NECESSARY WORK TO PROVIDE SUITABLE CONNECTIONS WITH ALL ROADS, STREETS, AND DRIVES ENTERING THIS PROJECT. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PARTICULAR ITEMS INVOLVED.

GUARDRAIL:

THE GUARDRAIL LOCATIONS SHOWN ON THE PLANS MAY BE ADJUSTED DURING CONSTRUCTION AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHOULD CONSULT WITH THE ENGINEER PRIOR TO ORDERING GUARDRAIL MATERIAL.

TEMPORARY SHORING:

SHORING REQUIRED FOR THE MAINTENANCE OF TRAFFIC NOT SHOWN ON THE PLANS WILL BE PAID FOR AT THE CONTRACT PRICE FOR "TEMPORARY SHORING".

SUBSURFACE PLANS:

SUBSURFACE PLANS ARE AVAILABLE FOR THE STRUCTURE ONLY. THE CONTRACTOR SHOULD MAKE HIS OWN INVESTIGATION AS TO THE OTHER SUBSURFACE CONDITIONS.

UTILITIES:

UTILITY OWNERS ON THIS PROJECT ARE DUKE ENERGY AND FRONTIER COMMUNICATION. ANY RELOCATION OF EXISTING UTILITIES WILL BE ACCOMPLISHED BY OTHERS.

RIGHT–OF–WAY MARKERS:

ALL RIGHT–OF–WAY MARKERS ON THIS PROJECT SHALL BE PLACED BY CONTRACT IN ACCORDANCE WITH SECTION 801 OF THE 2012 NORTH CAROLINA STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES.

6/2/99
3:43:45 PM
R:\3215\Bridge008\Roadway\Proj\17BP14R68_RDY_TYP.dgn
baross

PROJECT REFERENCE NO.	SHEET NO.
17BP.14.R.68	1-B

Note: Not to Scale

****S.U.E. = Subsurface Utility Engineering***

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

CONVENTIONAL PLAN SHEET SYMBOLS

BOUNDARIES AND PROPERTY:

- State Line
- County Line
- Township Line
- City Line
- Reservation Line
- Property Line
- Existing Iron Pin — EIP
- Property Corner
- Property Monument — ECM
- Parcel/Sequence Number — 123
- Existing Fence Line
- Proposed Woven Wire Fence
- Proposed Chain Link Fence
- Proposed Barbed Wire Fence
- Existing Wetland Boundary — WLB
- Proposed Wetland Boundary — WLB
- Existing High Quality Wetland Boundary — HQ WLB
- Existing Endangered Animal Boundary — EAB
- Existing Endangered Plant Boundary — EPB

BUILDINGS AND OTHER CULTURE:

- Gas Pump Vent or U/G Tank Cap
- Sign — S
- Well — W
- Small Mine
- Foundation
- Area Outline
- Cemetery
- Building
- School
- Church
- Dam

HYDROLOGY:

- Stream or Body of Water
- Hydro, Pool or Reservoir
- River Basin Buffer — RBB
- Flow Arrow
- Disappearing Stream
- Spring
- Swamp Marsh
- Proposed Lateral, Tail, Head Ditch — FLOW
- False Sump

RAILROADS:

- Standard Guage — CSX TRANSPORTATION
- RR Signal Milepost — MILEPOST 35
- Switch — SWITCH
- RR Abandoned
- RR Dismantled

RIGHT OF WAY:

- Baseline Control Point — BCP
- Existing Right of Way Marker
- Existing Right of Way Line
- Proposed Right of Way Line — RW
- Proposed Right of Way Line with Iron Pin and Cap Marker — RW
- Proposed Right of Way Line with Concrete or Granite Marker — RW
- Existing Control of Access — CA
- Proposed Control of Access — CA
- Existing Easement Line — E
- Proposed Temporary Construction Easement — E
- Proposed Temporary Drainage Easement — TDE
- Proposed Permanent Drainage Easement — PDE
- Proposed Permanent Utility Easement — PUE

ROADS AND RELATED FEATURES:

- Existing Edge of Pavement
- Existing Curb
- Proposed Slope Stakes Cut — C
- Proposed Slope Stakes Fill — F
- Proposed Wheel Chair Ramp — WCR
- Curb Cut for Future Wheel Chair Ramp — CCFR
- Existing Metal Guardrail
- Proposed Guardrail
- Existing Cable Guiderail
- Proposed Cable Guiderail
- Equaility Symbol
- Pavement Removal

VEGETATION:

- Single Tree
- Single Shrub
- Hedge
- Woods Line
- Orchard
- Vineyard — Vineyard

EXISTING STRUCTURES:

MAJOR:

- Bridge, Tunnel or Box Culvert — CONC
- Bridge Wing Wall, Head Wall and End Wall — CONC WW

MINOR:

- Head and End Wall — CONC HW
- Pipe Culvert
- Footbridge
- Drainage Box: Catch Basin, DI or JB — CB
- Paved Ditch Gutter
- Storm Sewer Manhole — S
- Storm Sewer — S

UTILITIES:

POWER:

- Existing Power Pole
- Proposed Power Pole
- Existing Joint Use Pole
- Proposed Joint Use Pole
- Power Manhole — P
- Power Line Tower
- Power Transformer
- U/G Power Cable Hand Hole — HH
- H-Frame Pole
- Recorded U/G Power Line — P
- Designated U/G Power Line (S.U.E.*) — P

TELEPHONE:

- Existing Telephone Pole
- Proposed Telephone Pole
- Telephone Manhole — T
- Telephone Booth
- Telephone Pedestal — T
- Telephone Cell Tower
- U/G Telephone Cable Hand Hole — HH
- Recorded U/G Telephone Cable — T
- Designated U/G Telephone Cable (S.U.E.*) — T
- Recorded U/G Telephone Conduit — TC
- Designated U/G Telephone Conduit (S.U.E.*) — TC
- Recorded U/G Fiber Optics Cable — T FO
- Designated U/G Fiber Optics Cable (S.U.E.*) — T FO

WATER:

- Water Manhole — W
- Water Meter
- Water Valve
- Water Hydrant
- Recorded U/G Water Line — W
- Designated U/G Water Line (S.U.E.*) — W
- Above Ground Water Line — A/G Water

TV:

- TV Satellite Dish
- TV Pedestal — C
- TV Tower
- U/G TV Cable Hand Hole — HH
- Recorded U/G TV Cable — TV
- Designated U/G TV Cable (S.U.E.*) — TV
- Recorded U/G Fiber Optic Cable — TV FO
- Designated U/G Fiber Optic Cable (S.U.E.*) — TV FO

GAS:

- Gas Valve
- Gas Meter
- Recorded U/G Gas Line — G
- Designated U/G Gas Line (S.U.E.*) — G
- Above Ground Gas Line — A/G Gas

SANITARY SEWER:

- Sanitary Sewer Manhole
- Sanitary Sewer Cleanout
- U/G Sanitary Sewer Line — SS
- Above Ground Sanitary Sewer — A/G Sanitary Sewer
- Recorded SS Forced Main Line — FSS
- Designated SS Forced Main Line (S.U.E.*) — FSS

MISCELLANEOUS:

- Utility Pole
- Utility Pole with Base
- Utility Located Object
- Utility Traffic Signal Box — S
- Utility Unknown U/G Line — ?UTL
- U/G Tank; Water, Gas, Oil
- A/G Tank; Water, Gas, Oil
- U/G Test Hole (S.U.E.*)
- Abandoned According to Utility Records — AATUR
- End of Information — E.O.I.

PROJECT REFERENCE NO.	SHEET NO.
17BPJ4.R.68	1-C

SURVEY CONTROL SHEET 17BP.14.R.68



DATUM DESCRIPTION

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCGS FOR MONUMENT "550008 BL-3"
WITH NAD 83/NSRS 2007 STATE PLANE GRID COORDINATES OF NORTHING: 553573.3180(ft) EASTING: 723699.4320(ft)
ELEVATION: 2207.71(ft)
THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.999771964
THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "550008 BL-3" TO -L- STATION 10+00 IS
S76°47'12"E 537.2403'
ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES
VERTICAL DATUM USED IS NAVD 88

BL

POINT	DESC.	NORTH	EAST	ELEVATION	EL STATION	OFFSET
1	BL-1	553471.4664	723238.0185	2205.60	10+64.32	9.87 LT
2	BL-2	553519.2800	723492.8683	2206.68	13+23.60	12.42 LT
3	BL-3	553573.3180	723699.4320	2207.71	15+37.73	11.33 RT

BM1 ELEVATION = 2205.51
N 553475 E 723513
BL STATION 7+67.91 48.40 RIGHT
RR SPIKE IN 15" BIRCH TREE

Scale 1" = 50'

50' 0 50' 100'

STRUCTURE: 55-0008
COUNTY: MACON

6/2/99
9:05:52 AM
R:\3215\Bridge008\Roadway\Proj\17BP14R68_LS_PSH.dgn
baross

PROJECT REFERENCE NO.	SHEET NO.
17BPJ4.R.68	2

ROADWAY DESIGN ENGINEER — PAVEMENT DESIGN ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. VOSO

NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. VOSO

PLANS PREPARED BY:

Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

6/2/99

1:15:08 PM 17BP14R68_RDY_TYP.dgn

PAVEMENT SCHEDULE

ITEM	DESCRIPTION	ITEM	DESCRIPTION
C1	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD. IN EACH OF 2 LAYERS.	T	EARTH MATERIAL.
C2	PROP. VARIABLE DEPTH S9.5B ASPHALT CONCRETE SURFACE COURSE, AT AN AVERAGE RATE OF 112 LBS PER SY. YD. AT 1" DEPTH. TO BE PLACED IN LAYERS NOT TO EXCEED 2" IN DEPTH.	U	EXISTING PAVEMENT.
E1	PROP. APPROX. 5" ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 570 LBS. PER SQ. YD.		

NOTE: ALL PAVEMENT EDGE SLOPES ARE TO BE 1:1



USE TYPICAL SECTION No. 1

-L- STA. 10+50.00 TO STA. 12+92.80 (Begin Bridge)
-L- STA. 13+22.80 (End Bridge) TO STA. 15+80.00

TYPICAL SECTION NO. 1



INLET CHANNEL
(NOT TO SCALE)



CULVERT INTERNAL CHANNEL
(NOT TO SCALE)



OUTLET CHANNEL
(NOT TO SCALE)



TYPICAL SECTION ALONG -L- ℄



TYPICAL SECTION ON BRIDGE

-L- STA. 12+92.80 (BEGIN BRIDGE) TO 13+22.80 (END BRIDGE)

PROJECT REFERENCE NO.	SHEET NO.
17BP.14.R.68	3

ROADWAY DESIGN ENGINEER

PAVEMENT DESIGN ENGINEER

PLANS PREPARED BY:
Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

SUMMARY OF QUANTITIES

Line Item	Des	Sec No.	Description	Quantity	Unit
0000100000-N	M	800	MOBILIZATION	1.00	LS
0000400000-N	M	801	CONSTRUCTION SURVEYING	1.00	LS
0008000000-E	G	226	SUPP CLEARING & GRUBBING	1.00	ACR
0043000000-N	G	226	GRADING	1.00	LS
0057000000-E	G	226	UNDERCUT EXCAVATION	50.00	CY
0195000000-E	G	SP	SELECT GRANULAR MATERIAL	50.00	CY
0199000000-E	M	SP	TEMPORARY SHORING	362.00	SF
1220000000-E	G	545	INCIDENTAL STONE BASE	50.00	TON
1489000000-E	P	610	ASP CONC BASE CRS B25.0B	360.00	TON
1519000000-E	P	610	ASP CONC SURF CRS S9.5B	220.00	TON
1575000000-E	P	620	ASP FOR PLANT MIX	30.00	TON
3030000000-E	GR	862	STL BM GUARDRAIL	175.00	LF
3150000000-N	GR	862	ADDIT GUARDRAIL POSTS	10.00	EA
3165000000-N	GR	862	GR ANCHOR TYPE 350 TL-2	4.00	EA
3380000000-E	Y	862	TEMP STL BM GUARDRAIL	50.00	LF
3569000000-E	R	867	BARBED WIRE FENCE RESET	450.00	LF
4400000000-E	Y	1110	WORK ZONE SIGNS (STAT)	184.00	SF
4410000000-E	Y	1110	WORK ZONE SIGNS (BARR)	20.00	SF
4430000000-N	Y	1130	DRUMS	29.00	EA
4445000000-E	Y	1145	BARRICADES (TYPE III)	16.00	LF
4455000000-N	Y	1150	FLAGGER	5.00	DAY
4465000000-N	Y	1160	TEMPORARY CRASH CUSHIONS	2.00	EA
4470000000-N	Y	1160	RESET CRASH CUSHION	2.00	EA
4485000000-E	Y	1170	PORT CONC BARRIER	40.00	LF
4500000000-E	Y	1170	RESET PORT CONC BARRIER	40.00	LF
4810000000-E	PM	1205	PAINT PVMT MARKINGS 4"	5460.00	LF
4835000000-E	PM	1205	PAINT PVT MKG LINES 24"	20.00	LF
4850000000-E	PM	1205	LINE REMOVAL 4" WIDE	200.00	LF
4870000000-E	PM	1205	LINE REMOVAL 24" WIDE	20.00	LF
6000000000-E	L	1605	TEMPORARY SILT FENCE	1210.00	LF
6009000000-E	L	1610	EROS CONTRL STONE CL B	100.00	TON
6012000000-E	L	1610	SEDIMENT CONTROL STONE	40.00	TON
6015000000-E	L	1615	TEMPORARY MULCHING	1.00	ACR
6018000000-E	L	1620	SEED FOR TEMP SEEDING	50.00	LB
6021000000-E	L	1620	FERT FOR TEMP SEEDING	0.25	TON
6024000000-E	L	1622	TEMPORARY SLOPE DRAINS	100.00	LF
6029000000-E	L	SP	SAFETY FENCE	100.00	LF
6030000000-E	L	1630	SILT EXCAVATION	120.00	CY
6036000000-E	L	1631	MATTING FOR EROS CONTROL	2200.00	SY
6037000000-E	L	SP	COIR FIBER MAT	150.00	SY
6042000000-E	L	1632	1/4" HARDWARE CLOTH	115.00	LF
6051000000-E	L	SP	WILDFLWR SEED & MULCH	0.25	ACR
6070000000-N	L	1639	SPECIAL STILLING BASINS	1.00	EA
6071012000-E	L	SP	COIR FIBER WATTLE	35.00	LF
6071020000-E	L	SP	POLYACRYLAMIDE (PAM)	5.00	LB
6084000000-E	L	1660	SEEDING AND MULCHING	0.70	ACR
6090000000-E	L	1661	SEED FOR REPAIR SEEDING	50.00	LB
6093000000-E	L	1661	FERT FOR REPAIR SEEDING	0.25	TON
6096000000-E	L	1662	SEED FOR SUPP SEEDING	50.00	LB
6108000000-E	L	1665	FERTILIZER TOPDRESSING	0.75	TON
6117000000-N	L	SP	RESPONSE FOR EROS CONTROL	7.00	EA
6118000000-N	L	SP	ROOTWADS	15.00	EA
6123000000-E	L	1670	REFORESTATION	1.00	ACR
6126000000-E	L	SP	STREAMBANK REFORESTATION	0.23	ACR
6132000000-N	L	SP	ROCK CROSS VANE	5.00	EA
6132000000-N	L	SP	CONSTRUCTED RIFFLE	5.00	EA
6138000000-E	L	SP	STREAM PLUG	100.00	CY
7980000000-N	Z	SP	PORTABLE PRE-TIMED TRAFFIC SIGNAL	1.00	EA
8035000000-N	B	402	REMV EXIST STR 13+10	1.00	LS
8121000000-N	B	412	UNCL STR EXCAV STA 13+10	1.00	LS
8182000000-E	B	420	CLASS A CONCRETE (BRIDGE)	23.00	CY
8217000000-E	B	425	REINF STEEL (BRIDGE)	788.00	LB
8608000000-E	B	876	RIP RAP II (2'-0")	110.00	TON
8860000000-N	B	SP	30'x30' PRECAST CROWNSPAN OR EQUIV. W/ HEADWALL & WINGWALLS	1.00	LS
8622000000-E	B	876	GEOTEXTILE FOR DRAINAGE	120.00	SY

6/21/00

COMPUTED BY: BGR	DATE: 2-14-13
CHECKED BY: JBV	DATE: 2-14-13

PROJECT REFERENCE NO.	SHEET NO.
17BP.14.R.68	3-A

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

"N" = DISTANCE FROM EDGE OF LANE TO FACE OF GUARDRAIL.
TOTAL SHOULDER WIDTH = DISTANCE FROM EDGE OF TRAVEL LANE TO SHOULDER BREAK POINT.
FLARE LENGTH = DISTANCE FROM LAST SECTION OF PARALLEL GUARDRAIL TO END OF GUARDRAIL.
W = TOTAL WIDTH OF FLARE FROM BEGINNING OF TAPER TO END OF GUARDRAIL.
G = GATING IMPACT ATTENUATOR TYPE 350
NG = NON-GATING IMPACT ATTENUATOR TYPE 350

GUARDRAIL SUMMARY

SURVEY LINE	BEG. STA.	END STA.	LOCATION	LENGTH			WARRANT POINT		"N" DIST. FROM E.O.L.	TOTAL SHOUL. WIDTH	FLARE LENGTH		W		ANCHORS									IMPACT ATTENUATOR TYPE 350			SINGLE FACED GUARDRAIL	REMOVE EXISTING GUARDRAIL	REMOVE AND STOCKPILE EXISTING GUARDRAIL	REMARKS
				STRAIGHT	SHOP CURVED	DOUBLE FACED	APPROACH END	TRAILING END			APPROACH END	TRAILING END	APPROACH END	TRAILING END	XI MOD	XI	GRAU 350 TYPE TL-2	M-350	TYPE III	CAT-1	VI MOD	BIC	AT-1	EA	G	NG				
-L-	12+43.00	13+73.00	LT	130			BRIDGE	BRIDGE	3.00	6		31.25		0.625			2													
-L-	12+43.00	13+73.00	RT	130			BRIDGE	BRIDGE	3.00	6	31.25		0.625				2													
			TOTAL	260.00													4													
		DEDUCT ANCHORS	TYPE TL-2 – 25.00	-100																										
			TOTAL	160.00																										
ADDITIONAL GUARDRAIL POSTS = 10			SAY	175.00													4													

LIST OF PIPES, ENDWALLS, ETC. (FOR PIPES 48" & UNDER)

STATION / SIZE / THICKNESS OR GAUGE	LOCATION (LT,RT, OR CL)	STRUCTURE NO. FROM	STRUCTURE NO. TO	TOP ELEVATION	INVERT ELEVATION	INVERT ELEVATION	SLOPE CRITICAL	DRAINAGE PIPE (RCP, CSP, CAAP, HDPE, or PVC) 12"	15"	18"	24"	30"	36"	42"	48"	C.S. PIPE (UNLESS NOTED OTHRWISE) 12" .064	15" .064	18" .064	24" .064	24"	30" .079	30"	36" .079	36"	42" .109	42"	48" .109	48"	CLASS III R.C. PIPE (UNLESS OTHERWISE NOTED) 12"	15"	18"	24"	30"	36"	42"	48"	15" SIDE DRAIN PIPE	18" SIDE DRAIN PIPE	24" SIDE DRAIN PIPE	ENDWALLS STD. 838.01, STD. 838.11 OR STD. 838.80 (UNLESS NOTED OTHERWISE) CU. YDS. R.C.P.	C.S.P.	QUANTITIES FOR DRAINAGE STRUCTURES * TOTAL L.F. FOR PAY QUANTITY SHALL BE COL. 'A' + (1.3 X COL.'B') PER EACH (0' THRU 5.0')	LIN. *FT. A 5.0' THRU 10.0'	B 10.0' AND ABOVE	C.B. STD. 840.01 OR STD. 840.02	FRAME, GRATES AND HOOD STANDARD 840.03 TYPE OF GRATE E	F	G		D.I. STD. 840.14 OR STD. 840.15	D.I. FRAME & GRATE STD. 840.16	G.D.I. TYPE "A" STD. 840.17 OR 840.26	G.D.I. TYPE "B" STD. 840.18 OR 840.27	G.D.I. TYPE "D" STD. 840.19 OR 840.28	G.D.I. FRAME WITH GRATE STD. 840.22	G.D.I. FRAME WITH TWO GRATES STD. 840.22	G.D.I. (N.S.) FRAME WITH GRATE STD. 840.24	G.D.I. (N.S.) FRAME WITH TWO GRATES STD. 840.24	J.B. STD. 840.31 OR 840.32								CORR. STEEL ELBOWS NO. & SIZE	CONC. COLLARS CL. "B" C.Y. STD 840.72	CONC. & BRICK PIPE PLUG, C.Y. STD. 840.71	PIPE REMOVAL LIN.FT.	REMARKS

ABBREVIATIONS

C.B. CATCH BASIN
N.D.I. NARROW DROP INLET
D.I. DROP INLET
G.D.I. GRATED DROP INLET
G.D.I. (N.S.) GRATED DROP INLET (NARROW SLOT)
J.B. JUNCTION BOX
M.H. MANHOLE
T.B.D.I. TRAFFIC BEARING DROP INLET
T.B.J.B. TRAFFIC BEARING JUNCTION BOX

Note: Invert elevations are for bid purposes only. Contractor to field verify all existing and proposed elevations

PAVEMENT REMOVAL SUMMARY

SURVEY LINE	STATION	STATION	LOCATION LT/RT/CL	YD^2
-L-	10+50	15+80	CL	1,001
			TOTAL:	1,001
			SAY:	1,050

Approximate quantities only. Unclassified excavation, borrow excavation, shoulder borrow, fine grading, clearing and grubbing, breaking of existing pavement and removal of existing pavement will be paid for at the lump sum price for "Grading".

SUMMARY OF EARTHWORK
IN CUBIC YARDS

LOCATION	UNCLASSIFIED EXCAVATION	UNDERCUT	EMBT+%	BORROW	WASTE
-CHANNEL- 10+00 TO 10+50	31		0	0	31
-CHANNEL- 10+50 TO 11+00	82		0	0	82
-CHANNEL- 11+00 TO 11+50	43		0	0	43
-CHANNEL- 11+50 TO 11+85.44	8		0	0	8
-L- 10+50 TO 11+00	0		17	17	0
-L- 11+00 TO 11+50	18		39	21	0
-L- 11+50 TO 12+00	468		37	0	431
-L- 12+00 TO 12+50	728		25	0	703
-L- 12+50 TO 13+00	361		10	0	351
-L- 13+00 TO 13+50	119		83	0	36
-L- 13+50 TO 14+00	16		171	155	0
-L- 14+00 TO 14+50	0		129	129	0
-L- 14+50 TO 15+00	10		65	55	0
-L- 15+00 TO 15+50	0		30	30	0
-L- 15+50 TO 15+80	0		4	4	0
TOTALS	1884		610	411	1685
EARTH WASTE TO REPLACE BORROW				-411	-411
GRAND TOTAL	1884			0	1274
SAY	1900				1300
ESTIMATED CONTINGENCY:					
UNDERCUT EXCAVATION = 50					
SELECT GRANULAR MATIERIAL = 50					
INCIDENTAL STONE BASE = 50					

9:42:49 AM
R:\3215\Bridge008\Roadway\Proj\17BP14R68_RDY_TYP.dgn
bgross

5/14/99

PROJECT REFERENCE NO.	SHEET NO.
17BPJ4.R.68	4
R/W SHEET NO.	

ROADWAY DESIGN ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. YOSO

HYDRAULICS ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 026945 ENGINEER DINA J. BOLDEN

Prepared in the Office of:

Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

50 25 0 50 100
SCALE



SKETCH SHOWING THE RELATIONSHIP OF THE BRIDGE TO THE PAVEMENT

25 0 25 50

FOR STRUCTURE PLANS SEE SHEET S-1 THRU S-7

-L-

PI Sta 11+00.00	PI Sta 12+25.09	PI Sta 14+86.62
Δ = 2° 17' 26.2" (RT)	Δ = 2° 17' 26.2" (LT)	Δ = 35° 10' 18.4" (LT)
D = 2° 17' 30.6"	D = 2° 17' 30.6"	D = 11° 27' 33.0"
L = 99.95'	L = 99.95'	L = 306.93'
T = 49.98'	T = 49.98'	T = 158.47'
R = 2,500.00'	R = 2,500.00'	R = 500.00'
SE = VARIES	SE = .02	SE = .04
	V = 35MPH	V = 60MPH



DETAIL 1

SPECIAL CUT DITCH

(Not to Scale)



FROM STA. 11+00 TO STA. 12+95 RT

12:56:04 PM
J:\3215\Bridge\Roadway\Proj\17BP14R68_RDY_PSH.dgn

5/14/99

PROJECT REFERENCE NO.	SHEET NO.
17BPJ4.R.68	5

ROADWAY DESIGN ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 022559 ENGINEER JAMES B. VOSO

HYDRAULICS ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 028945 ENGINEER JOHN J. BOLDEN 6/16/12

Prepared in the Office of:

Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
2 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

50 25 0 50 100
PROFILE (HORIZONTAL)
10 5 0 10 20
PROFILE (VERTICAL)
SCALE



BRIDGE HYDRAULIC DATA

DESIGN DISCHARGE	=	1100	CFS
DESIGN FREQUENCY	=	25	YRS
DESIGN HW ELEVATION	=	2203.7	FT
BASE DISCHARGE	=	1840	CFS
BASE FREQUENCY	=	100	YRS
BASE HW ELEVATION	=	2205.75	FT
OVERTOPPING DISCHARGE	=	1800	CFS
OVERTOPPING FREQUENCY	=	200+/-	YRS
OVERTOPPING ELEVATION	=	2207.7	FT
DATE OF SURVEY	=	9-10-2010	
W.S. ELEVATION AT DATE OF SURVEY	=	2197.70	FT

10:39:55 AM
R:\3215\Bridge008\Roadway\Proj\17BP14R68_RDY_PSH.dgn
Default

05/08/99

TIP PROJECT: 17BP.14.R.68

CONTRACT:



VICINITY MAP

See Sheet 1-A For Index of Sheets
See Sheet 1-B For Conventional Symbols

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.14.R.68	RE-1	

STATE PROJ. NO.	F. A. PROJ. NO.	DESCRIPTION
17BP.14.R.68		PE, R/W, UTIL
17BP.14.R.68		CONST.

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

MACON COUNTY

LOCATION: BRIDGE 008 (OVER ELLIJAY CREEK) ON SR 1001 (ELLIJAY RD.)

TYPE OF WORK: GRADING, PAVING, DRAINAGE & STRUCTURE

STREAM RELOCATION PLANS



CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II.

GRAPHIC SCALES

50 25 0 50 100
PLANS

50 25 0 50 100
PROFILE (HORIZONTAL)

10 5 0 10 20
PROFILE (VERTICAL)

DESIGN DATA

ADT (2008)= 520

V = 35 MPH

FUNC CLASS = LOCAL
SUB–REGIONAL TIER

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT 17BP.14.R.68	=	*0.0944 MI*
LENGTH STRUCTURE TIP PROJECT 17BP.14.R.68	=	*0.006 MI*
TOTAL LENGTH TIP PROJECT 17BP.14.R.68	=	*0.1004 MI*

NCDOT CONTACT: JOSHUA DEYTON, P.E.
PROJECT ENGINEER

Prepared In the Office of:
Mattern & Craig
CONSULTING ENGINEERS – SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 – FAX (828) 254-4562

2012 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE: AUGUST 1, 2013

LETTING DATE: FEBRUARY, 2014

JAMES B. VOSO, P.E.
PROJECT ENGINEER

MATT CLABAUGH, P.E.
PROJECT DESIGN ENGINEER

HYDRAULICS ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 028945 ENGINEER DANA J. BOLDEN

SIGNATURE:

ROADWAY DESIGN ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. VOSO

SIGNATURE: P.E.

DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA

STATE OF NORTH CAROLINA • DEPARTMENT OF TRANSPORTATION •

P.E.
STATE HIGHWAY DESIGN ENGINEER

12:59:30 PM
R:\3215\Bridge008\Roadway\Proj\17BP14R68_REU_TSH.dgn
bgross

PROJECT REFERENCE NO.	SHEET NO.
17BP.14.R.68	RE-2
R/W SHEET NO.	

ROADWAY DESIGN ENGINEER — NORTH CAROLINA PROFESSIONAL SEAL 022339 ENGINEER JAMES B. VOSS

HYDRAULICS ENGINEER — NORTH CAROLINA PROFESSIONAL SEAL 028945 ENGINEER DANA J. BOLDEN

8/17/99

REVISIONS

BM #1
-BL- STA 7+67.91
48.40' RT
ELEV=2205.51'

NAD 83/
NSRS 2007

10 5 0 10 20
PLAN

BEGIN CHANNEL CHANGE
-L- STA 13+07.05
28.90' RT

POT Sta. 10+00.00

10+00

S 86° 59' 01.1" E

PT Sta. R1
10+53.96

PC Sta. 10+67.06

S 80° 33' 55.8" E

PI Sta. 10+84.19

N 34° 00' 18.1" E

PT Sta. 11+05.34

PC Sta. 11+37.41

PERRY PRONG
ELIJAY CREEK

ROCK CROSS VANE (TYP.)

ROOT WAD (TYP.)

PT Sta. 11+23.72

PC Sta. 11+41.51

N 46° 46' 31.7" E

CONSTRUCTED RIFFLE (TYP.)

S 83° 26' 54.9" E

PT Sta. 11+58.89

POT Sta. 11+85.44

STREAM PLUG

END CHANNEL CHANGE
-L- STA 14+60.40
54.14' RT

R1 553467.18035603 723523.71979421
R2 553462.94443278 723553.43190141
R3 553494.00423584 723580.03219743
R4 553477.03798040 723620.38664204

6' BANKFULL WIDTH
1' MAX. DEPTH
2'-0" 2:1 2'-0" 2:1 2'-0" 2:1
EXISTING GROUND
EROSION CONTROL MATTING
LIVE STAKES

TYPICAL STREAM CROSS-SECTION
(NOT TO SCALE)

LEGEND
- CONSTRUCTED RIFFLE
- ROOT WAD
- STREAM PLUG
- ROCK CROSS VANE

CHANNEL

PI Sta 10+47.30	PI Sta 10+76.70	PI Sta 11+15.24	PI Sta 11+50.79
Δ = 79° 00' 40.8" (LT)	Δ = 65° 25' 46.1" (RT)	Δ = 52° 39' 32.5" (LT)	Δ = 49° 46' 33.3" (RT)
D = 47° 27' 53.4"	D = 38° 58' 18.7"	D = 286° 28' 44.0"	D = 286° 28' 44.0"
L = 16.55'	L = 17.13'	L = 18.38'	L = 17.38'
T = 9.89'	T = 9.64'	T = 9.90'	T = 9.28'
R = 12.00'	R = 15.00'	R = 20.00'	R = 20.00'

STREAM RADIUS COORDINATES

	NORTHING	EASTING
R1	553467.18035603	723523.71979421
R2	553462.94443278	723553.43190141
R3	553494.00423584	723580.03219743
R4	553477.03798040	723620.38664204

BM1 ELEVATION = 2205.51
N 553475 E 723513
BL STATION 7+67.91 48.40 RIGHT
RR SPIKE IN 15" BIRCH TREE

10 5 0 10 20
PROFILE (HORIZONTAL)
2 1 0 2 4
PROFILE (VERTICAL)
SCALE

NOTE: GRADING FOR THE STREAM RELOCATION IS INCIDENTAL TO LUMP SUM GRADING

10+00 10+50 11+00 11+50 12+00

2,207
2,203
2,199
2,195

EXISTING GROUND
END CHANNEL
ELEV = 2198.89
CONSTRUCTED RIFFLE (TYP)
SEE PLAN VIEW
.662%
0.0%
TYPICAL POOL
CONSTRUCTED RIFFLE (TYP)
SEE PLAN VIEW
PROPOSED ALIGNMENT
STREAM BOTTOM
BEGIN CHANNEL
ELEV = 2201.10

12:54:46 PM
R:\3215\Bridge008\Roadway\Proj\17BP14R68_REV_PSH.dgn

CHANNEL CONSTRUCTION SEQUENCE

PROJECT REFERENCE NO.	SHEET NO.
17BP.14.R.68	RE-3
R/W SHEET NO.	

ROADWAY DESIGN ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. VOSO

HYDRAULICS ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 028945 ENGINEER DANA J. BOLDEN

1. CONSTRUCT THE RELOCATED STREAM SECTION IN DRY CONDITIONS.
2. INSTALL A STREAM PLUG AT THE BEGINING AND END OF THE AREA BEING BUILT IN THE DRY. THESE PLUGS WILL BE REMOVED WHEN THE NEW CHANNEL IS STABILIZED WITH MATTING.
3. PROJECT WILL BE CONSTRUCTED FROM THE DOWNSTREAM END STARTING AT THE CONFLUENCE WITH BERRY PRONG OF ELIJAY CREEK WORKING IN THE UPSTREAM DIRECTION.
4. CONSTRUCT THE PROPOSED CHANNEL ACCORDING TO THE CONSTRUCTION PLANS. UTILIZE SPECIAL STILLING BASIN AS NECESSARY TO DE-WATER PROPOSED CHANNEL.
5. STOCKPILE AND SEPERATE ALL SOIL SUITABLE FOR FILL OR TOPSOIL.
6. INSTALL STRUCTURES (IE. CONSTRUCTED RIFFLES AND ROOT WADS).
7. SEED AREAS WITH SEED MIX AND MULCH WHERE COIR FIBER MATTING WILL BE INSTALLED.
8. INSTALL COIR FIBER MATTING.
9. PLANT VEGETATION ACCORDING TO CONSTRUCTION PLANS.
10. REMOVE THE TEMPORARY STREAM PLUGS FROM THE NEWLY CONSTRUCTED CHANNEL, AND DIVERT WATER INTO CONSTRUCTED CHANNEL.
11. INSTALL CHANNEL PLUG INTO ABANDONED CHANNEL.
12. FILL THE ABANDONED CHANNEL WITH SUITABLE MATERIAL APPROVED BY THE ENIGNEER.



PROJECT REFERENCE NO.	SHEET NO.
17BPJ4.R.68	RE-4
R/W SHEET NO.	

ROADWAY DESIGN ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 022595 ENGINEER JAMES B. VOSO

HYDRAULICS ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 028945 ENGINEER DINA J. BOLDEN

REVISIONS

8/17/95



TYPICAL PLAN



TYPICAL RIFFLE



TYPICAL POOL



TYPICAL RIFFLE WITH BANKFULL BENCH



TYPICAL POOL WITH BANKFULL BENCH



TYPICAL PROFILE



TYPICAL PROFILE FOR ARMORED RIFFLE SECTION



CROSS VANE CONSTRUCTION IN MEANDER-BEND PLAN VIEW

CHANNEL TYPICAL DETAIL

NOT TO SCALE

W_{bkf} = BANKFULL WIDTH
D_{max} = MAXIMUM DEPTH
W_b = BOTTOM WIDTH
W_{fpa} = FLOOD PRONE AREA WIDTH

CROSS-SECTION DIMENSIONS

REACH	RIFFLE W_{bkf}	RIFFLE D_{max}	RIFFLE W_b	RIFFLE W_{fpa}	POOL W_{bkf}	POOL D_{max}	POOL W_b	POOL W_{fpa}	Width/Depth Ratio
Sta. 10+16 - Sta. 11+78	6	1	2	20	7	1.5	2	20	9
Sta. - Sta.									
Sta. - Sta.									
Sta. - Sta.									
Sta. - Sta.									
Sta. - Sta.									
Sta. - Sta.									
Sta. - Sta.									

NOTES:
1. THE COORDINATES FOR EACH CENTER OF RADIUS (EX. "R1","R2") AND EACH HEAD OF RIFFLE (EX. "HR1", "HR2") ARE INDICATED ON THE PLAN SHEETS.

9:44:08 AM
R:\3215\Bridge008\Roadway\Proj\17BPJ4R68_REV_PSH.dgn
mmoss

PROJECT REFERENCE NO.	SHEET NO.
17BPJ4.R.68	RE-5
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. VOSO

NORTH CAROLINA PROFESSIONAL SEAL 028946 ENGINEER DANA J. BOLDEN

8/17/99

REVISIONS



PLAN VIEW

	BOULDER DIMENSIONS (FT)(M)		
STATION	HEIGHT	LENGTH	WIDTH



SECTION A-A



SECTION B-B

NOTES:
1. DEEPEST PART OF POOL TO BE IN LINE WITH WHERE VANE ARM TIES INTO BANKFULL.
2. DO NOT EXCAVATE POOL TOO CLOSE TO FOOTER BOULDERS.
3. CLASS "A" STONE CAN BE USED TO REDUCE VOIDS BETWEEN HEADERS AND FOOTERS.
4. COMPACT BANKFULL TO EXTENT POSSIBLE OR AT THE DIRECTION OF THE ENGINEER.
5. POOL DEPTH SHOULD BE 2 TO 3 TIMES BANKFULL DEPTH.

ROCK CROSS VANE DETAIL
NOT TO SCALE



PLAN VIEW



TYPICAL CROSS SECTION



ANCHOR OPTIONS

NOTES:
1. IN AREAS TO BE MATTED, ALL SEEDING, SOIL AMENDMENTS, AND SOIL PREPARATION MUST BE COMPLETED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS PRIOR TO PLACEMENT OF COIR FIBER MATTING.
2. REBAR OR STAPLES MAY BE USED IN PLACE OF WOODEN STAKES AS DIRECTED BY THE ENGINEER.

COIR FIBER MATTING DETAIL
NOT TO SCALE



PLAN VIEW



SECTION A-A



SECTION B-B



SECTION C-C

NOTE:
1. BOULDERS SHOULD BE NATIVE STONES OR SHOT ROCK, ANGULAR AND OBLONG, WITH AN AXIS APPROXIMATELY 3' L x 2.5' W x 2' D

REACH	
Wbkf (ft)(m)	6
Dmax (ft)(m)	1

CONSTRUCTED RIFFLE DETAIL
NOT TO SCALE



PLAN VIEW



SECTION A-A



SECTION B-B

NOTES:
1. CHANNEL BLOCK SHALL BE INSTALLED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS.
2. BLOCK SHOULD BE INSTALLED AT THE INTERFACE BETWEEN EXISTING CHANNEL AND PROPOSED CHANNEL.
3. BOTTOM OF BLOCK SHOULD BE A MINIMUM OF 1' BELOW THE INVERT OF THE EXISTING CHANNEL.
4. BLOCK SHOULD EXTEND A MINIMUM OF 10' BEYOND THE LIMITS OF THE EXISTING STREAM CHANNEL.
5. INSTALL EROSION CONTROL MATTING AND SEED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS IMMEDIATELY AFTER GRADING.
6. COMPACT BACKFILL TO EXTENT POSSIBLE OR AT THE DIRECTION OF THE ENGINEER.

STREAM PLUG
NOT TO SCALE



PLAN VIEW
DRIVE POINT METHOD



PLAN VIEW
TRENCHING METHOD



SECTION A-A

NOTES:

ORIENT ROOT WADS SO THAT THE STREAM FLOW MEETS THE ROOT WAD STRAIGHT ON, DEFLECTING THE WATER AWAY FROM THE BANK.

METHODS OF INSTALLATION:

DRIVE POINT METHOD:

SHARPEN THE END OF THE LOG BEFORE "DRIVING" AT A DOWNWARD ANGLE INTO THE BANK. BOULDER SHOULD BE PLACED ON EACH SIDE OF THE ROOT WAD TO PIN IT IN PLACE. THE BOULDERS SHALL BE APPROXIMATELY 3' X 2.5' X 2'. ONE-THIRD OF THE ROOT WAD SHOULD REMAIN BELOW NORMAL BASE FLOW CONDITIONS.

TRENCHING METHOD:

IF THE ROOT WAD CANNOT BE DRIVEN INTO THE BANK OR THE BANK NEEDS TO BE RECONSTRUCTED, THE TRENCHING METHOD SHOULD BE USED. THIS METHOD REQUIRES THAT A TRENCH BE EXCAVATED FOR THE LOG PORTION OF THE ROOT WAD. IN THIS CASE, FOOTER BOUDERS SHOULD BE INSTALLED UNDERNEATH THE ROOT WAD IN A TRENCH EXCAVATED PARALLEL TO THE BANK AND WELL BELOW THE STREAM BED. BOULDERS SHOULD BE PLACED ON EACH SIDE OF THE ROOTWAD TO PIN IT IN PLACE. THE BOULDERS SHOULD BE APPROXIMATELY 3' X 2.5' X 2'. ONE-THIRD OF THE ROOT WAD SHOULD REMAIN BELOW NORMAL BASE FLOW CONDITIONS.

ROOT WAD DETAIL
NOT TO SCALE

9:45:16 AM
R:\3215\Bridge008\Roadway\Proj\17BP14R68_REU_PSH.dgn
bgross

PROJECT REFERENCE NO.	SHEET NO.
17BP.14.R.68	RF-1
R/W SHEET NO.	

ROADWAY DESIGN ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 022539 ENGINEER JAMES B. VOSO

HYDRAULICS ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 028945 ENGINEER DANA I. BOLDEN

PLANTING DETAILS

LIVE STAKES PLANTING DETAIL





BANK STABILIZATION WITH LIVE STAKES

NOTE:
LIVE STAKES SHALL BE SPACED APPROXIMATELY 4 FEET ON CENTER
LIVE STAKES SHALL BE DRIVEN UNTIL APPROXIMATELY 3/4 OF LIVE STAKE IS WITHIN GROUND

BAREROOT PLANTING DETAIL DIBBLE PLANTING METHOD USING THE KBC PLANTING BAR



1. Insert planting bar as shown and pull handle toward planter.
2. Remove planting bar and place seedling at correct depth.
3. Insert planting bar 2 inches toward planter from seedling.
4. Pull handle of bar toward planter, firming soil at bottom.
5. Push handle forward firming soil at top.
6. Leave compaction hole open. Water thoroughly.

PLANTING NOTES:

PLANTING BAG
During planting, seedlings shall be kept in a moist canvas bag or similar container to prevent the root systems from drying.

KBC PLANTING BAR
Planting bar shall have a blade with a triangular cross section, and shall be 12 inches long, 4 inches wide and 1 inch thick at center.

ROOT PRUNING
All seedlings shall be root pruned, if necessary, so that no roots extend more than 10 inches below the root collar.

☐ TYPE 1 STREAMBANK REFORESTATION SHALL BE PLANTED 3 FT. TO 5 FT. ON CENTER, RANDOM SPACING, AVERAGING 4 FT. ON CENTER, APPROXIMATELY 2724 PLANTS PER ACRE.

☐ TYPE 2 STREAMBANK REFORESTATION SHALL BE PLANTED 6 FT. TO 10 FT. ON CENTER, RANDOM SPACING, AVERAGING 8 FT. ON CENTER, APPROXIMATELY 680 PLANTS PER ACRE.

☐ NOTE: TYPE 1 AND TYPE 2 STREAMBANK REFORESTATION SHALL BE PAID FOR AS "STREAMBANK REFORESTATION"

STREAMBANK REFORESTATION TYPICAL



STREAMBANK REFORESTATION

MIXTURE, TYPE, SIZE, AND FURNISH SHALL CONFORM TO THE FOLLOWING:

TYPE 1			
50%	SALIX NIGRA	BLACK WILLOW	2 ft – 3 ft LIVE STAKES
50%	CORNUS AMOMUM	SILKY DOGWOOD	2 ft – 3 ft LIVE STAKES
TYPE 2			
25%	LIRIODENDRON TULIPIFERA	TULIP POPLAR	12 in – 18 in BR
25%	PLATANUS OCCIDENTALIS	SYCAMORE	12 in – 18 in BR
25%	PRUNUS SEROTINA	BLACK CHERRY	12 in – 18 in BR
25%	BETULA NIGRA	RIVER BIRCH	12 in – 18 in BR

☐ SEE PLAN SHEETS FOR AREAS TO BE PLANTED

STREAMBANK REFORESTATION DETAIL SHEET 1 OF 2

N.C.D.O.T. - ROADSIDE ENVIRONMENTAL UNIT

PROJECT REFERENCE NO.	SHEET NO.
17BPJ4.R.68	RF-2
R/W SHEET NO.	

ROADWAY DESIGN ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 022593 ENGINEER JAMES B. VOSO

HYDRAULICS ENGINEER

SEAL 028945 ENGINEER DIANA J. BOLDEN



PLAN VIEW



TYPICAL CROSS SECTION





ANCHOR OPTIONS

COIR FIBER MATTING DETAIL

NOT TO SCALE

STREAMBANK REFORESTATION

DETAIL SHEET 2 OF 2

N.C.D.O.T. - ROADSIDE ENVIRONMENTAL UNIT

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

TRANSPORTATION MANAGEMENT PLAN

MACON COUNTY



INDEX OF SHEETS

SHEET NO.	TITLE
TMP-1	TITLE SHEET, AND INDEX OF SHEETS
TMP-1A	LIST OF APPLICABLE ROADWAY STANDARD DRAWINGS, LEGEND, AND TEMPORARY PAVEMENT MARKING
TMP-1B	TRANSPORTATION OPERATIONS PLAN: (MANAGEMENT STRATEGIES, GENERAL NOTES AND LOCAL NOTES)
TMP-1C	STANDARD TEMPORARY SHORING DETAILS
TMP-2	TEMPORARY TRAFFIC CONTROL PHASE I
TMP-3	TEMPORARY TRAFFIC CONTROL PHASE II & III
PMP-1	PAVEMENT MARKING PLAN

SHEET NO.
TMP-1

17BP.14.R.68

TIP PROJECT:

WORK ZONE SAFETY & MOBILITY
"from the MOUNTAINS to the COAST"

N.C.D.O.T. WORK ZONE TRAFFIC CONTROL
1561 MAIL SERVICE CENTER (MSC) RALEIGH, NC 27699-1561
750 N. GREENFIELD PARKWAY, GARNER, NC 27529 (DELIVERY)
PHONE: (919) 773-2800 FAX: (919) 771-2745

J. S. BOURNE, P.E. — STATE TRAFFIC MANAGEMENT ENGINEER
JAMES VOSO, P.E. — TRAFFIC CONTROL PROJECT ENGINEER
JASON SNAPP, P.E. — TRAFFIC CONTROL PROJECT DESIGN ENGINEER
BRIAN ROSS — TRAFFIC CONTROL DESIGN ENGINEER

DIVISION OF HIGHWAYS * STATE OF NORTH CAROLINA * DEPARTMENT OF TRANSPORTATION * WORK ZONE TRAFFIC CONTROL

Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

APPROVED: James Voso
DATE: 10/16/13

SEAL

9:49:15 AM
R:\3215\Bridge008\Traffic\TrafficControl\Roadway\17BP14R68_TC_TSH.dgn
bgross

PROJ. REFERENCE NO.	SHEET NO.
17BP.14.R.68	TMP-1A

ROADWAY STANDARD DRAWINGS

THE FOLLOWING ROADWAY STANDARDS AS SHOWN IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANAUARY 2012 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
1101.01	WORK ZONE WARNING SIGNS
1101.02	TEMPORARY LANE CLOSURES
1101.11	TRAFFIC CONTROL DESIGN TABLES
1110.01	STATIONARY WORK ZONE SIGNS
1130.01	DRUMS
1135.01	CONES
1145.01	BARRICADES
1150.01	FLAGGING DEVICES
1160.01	TEMPORARY CRASH CUSHION
1165.01	WORK VEHICLE LIGHTING SYSTEMS AND TMA DELINEATION
1170.01	PORTABLE CONCRETE BARRIER
1180.01	SKINNY - DRUM
1205.01	PAVEMENT MARKINGS - LINE TYPES AND OFFSETS
1205.02	PAVEMENT MARKINGS - TWO LANE AND MULTILANE ROADWAYS
1205.12	PAVEMENT MARKINGS - BRIDGES
1261.01	GUARDRAIL AND BARRIER DELINEATORS - INSTALLATION SPACING
1261.02	GUARDRAIL AND BARRIER DELINEATORS - TYPES AND MOUNTING
1262.01	GUARDRAIL END DELINEATION

LEGEND

GENERAL

- DIRECTION OF TRAFFIC FLOW
- DIRECTION OF PEDESTRIAN TRAFFIC FLOW
- EXIST. PVMT.
- NORTH ARROW
- PROPOSED PVMT.
- WORK AREA
- REMOVAL
- USER DEFINED (IF NEEDED)
- USER DEFINED (IF NEEDED)

TRAFFIC CONTROL DEVICES

- BARRICADE (TYPE III)
- CONE
- DRUM SKINNY DRUM TUBULAR MARKER
- TEMPORARY CRASH CUSHION
- FLASHING ARROW BOARD
- FLAGGER
- LAW ENFORCEMENT
- TRUCK MOUNTED ATTENUATOR (TMA)
- CHANGEABLE MESSAGE SIGN

TEMPORARY SIGNING

- PORTABLE SIGN
- STATIONARY SIGN
- STATIONARY OR PORTABLE SIGN

SIGNALS

EXISTING PROPOSED TEMP TEMPORARY

PAVEMENT MARKINGS

- EXISTING LINES
- TEMPORARY LINES

PAVEMENT MARKERS

- CRYSTAL/CRYSTAL
- CRYSTAL/RED
- YELLOW/YELLOW

PAVEMENT MARKING SYMBOLS

PAVEMENT MARKING SYMBOLS

TEMPORARY PAVEMENT MARKING

SYMBOL	DESCRIPTION	PAY ITEM
PA	WHITE EDGELINE 1X	PAINT (4")
P2	WHITE STOP BAR 1X	PAINT (24")

Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

APPROVED: _____ DATE: 10/16/13

NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. VOSO

DIVISION OF HIGHWAYS · STATE OF NORTH CAROLINA · DEPARTMENT OF TRANSPORTATION · WORK ZONE TRAFFIC CONTROL

ROADWAY STANDARD DRAWINGS & LEGEND

PROJ. REFERENCE NO.	SHEET NO.
17BP.14.R.68	TMP-1B

GENERAL NOTES / LOCAL NOTES

GENERAL NOTES

CHANGES MAY BE REQUIRED WHEN PHYSICAL DIMENSIONS IN THE DETAIL DRAWINGS, STANDARD DETAILS, AND ROADWAY DETAILS ARE NOT ATTAINABLE TO MEET FIELD CONDITIONS OR RESULT IN DUPLICATE OR UNDESIRED OVERLAPPING OF DEVICES, MODIFICATION MAY INCLUDE: MOVING, SUPPLEMENTING, COVERING, OR REMOVAL OF DEVICES AS DIRECTED BY THE ENGINEER

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT, EXCEPT WHEN OTHERWISE NOTED IN THE PLAN, OR DIRECTED BY THE ENGINEER.

TIME RESTRICTIONS

A. DO NOT CONDUCT ANY HAULING OPERATIONS AGAINST THE FLOW OF TRAFFIC OF AN OPEN TRAVELWAY UNLESS THE HAULING OPERATION IS PROTECTED BY BARRIER OR GUARDRAIL OR AS DIRECTED BY THE ENGINEER.

LANE AND SHOULDER CLOSURE REQUIREMENTS

B. REMOVE LANE CLOSURE DEVICES FROM THE LANE WHEN WORK IS NOT BEING PERFORMED BEHIND THE LANE CLOSURE OR WHEN A LANE CLOSURE IS NO LONGER NEEDED OR AS DIRECTED BY THE ENGINEER.

C. WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO AN UNDIVIDED FACILITY AND WITHIN 5 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE USING ROADWAY STANDARD DRAWING NO. 1101.02 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.

D. WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN A LANE OF TRAVEL OF AN UNDIVIDED OR DIVIDED FACILITY, CLOSE THE LANE ACCORDING TO THE TRAFFIC CONTROL PLANS, ROADWAY STANDARD DRAWINGS, OR AS DIRECTED BY THE ENGINEER. CONDUCT THE WORK SO THAT ALL PERSONNEL AND/OR EQUIPMENT REMAIN WITHIN THE CLOSED TRAVEL LANE.

E. DO NOT WORK SIMULTANEOUSLY WITHIN 15 FT ON BOTH SIDES OF AN OPEN TRAVELWAY, RAMP, OR LOOP WITHIN THE SAME LOCATION UNLESS PROTECTED WITH GUARDRAIL OR BARRIER.

PAVEMENT EDGE DROP OFF REQUIREMENTS

F. BACKFILL AT A 6:1 SLOPE UP TO THE EDGE AND ELEVATION OF EXISTING PAVEMENT IN AREAS ADJACENT TO AN OPENED TRAVEL LANE THAT HAS AN EDGE OF PAVEMENT DROP-OFF AS FOLLOWS:

BACKFILL DROP-OFFS THAT EXCEED 2 INCHES ON ROADWAYS WITH POSTED SPEED LIMITS OF 45 MPH OR GREATER.

BACKFILL DROP-OFFS THAT EXCEED 3 INCHES ON ROADWAYS WITH POSTED SPEED LIMITS LESS THAN 45 MPH.

BACKFILL WITH SUITABLE COMPACTED MATERIAL, AS APPROVED BY THE ENGINEER, AT NO EXPENSE TO THE DEPARTMENT.

G. DO NOT EXCEED A DIFFERENCE OF 2 INCHES IN ELEVATION BETWEEN OPEN LANES OF TRAFFIC FOR NOMINAL LIFTS OF 1.5 INCHES. INSTALL ADVANCE WARNING "UNEVEN LANES" SIGNS (W8-11) 500 FT IN ADVANCE AND A MINIMUM OF EVERY HALF MILE THROUGHOUT THE UNEVEN AREA.

TRAFFIC PATTERN ALTERATIONS

H. NOTIFY THE ENGINEER TWENTY ONE (21) CALENDAR DAYS PRIOR TO ANY TRAFFIC PATTERN ALTERATION.

SIGNING

I. INSTALL ADVANCE WORK ZONE WARNING SIGNS WHEN WORK IS WITHIN 40 FT FROM THE EDGE OF TRAVEL LANE AND NO MORE THAN THREE (3) DAYS PRIOR TO THE BEGINNING OF CONSTRUCTION.

J. CONTRACTOR TO INSTALL SIGNING AND DEVICES REQUIRED TO CLOSE THE ROAD ACCORDING TO THE ROADWAY STANDARD DRAWINGS AND TRAFFIC CONTROL PLANS. CONTRACTOR TO INSTALL SIGNING REQUIRED FOR THE OFF-SITE DETOUR ROUTE AS SHOWN IN THE TRAFFIC CONTROL PLANS.

K. ENSURE ALL NECESSARY SIGNING IS IN PLACE PRIOR TO ALTERING ANY TRAFFIC PATTERN.

TRAFFIC BARRIER

L. INSTALL TEMPORARY BARRIER ACCORDING TO THE TRANSPORTATION MANAGEMENT PLANS A MAXIMUM OF TWO (2) WEEKS PRIOR TO BEGINNING WORK IN ANY LOCATION. ONCE TEMPORARY BARRIER IS INSTALLED AT ANY LOCATION PROCEED IN A CONTINUOUS MANNER TO COMPLETE THE PROPOSED WORK IN THAT LOCATION UNLESS OTHERWISE STATED IN THE TRANSPORTATION MANAGEMENT PLANS OR AS DIRECTED BY THE ENGINEER.

DO NOT PLACE BARRIER DIRECTLY ON ANY SURFACE OTHER THAN ASPHALT OR CONCRETE.

ONCE TEMPORARY BARRIER IS INSTALLED AT ANY LOCATION AND NO WORK IS PERFORMED BEHIND THE TEMPORARY BARRIER FOR A PERIOD LONGER THAN TWO (2) MONTHS, REMOVE / RESET TEMPORARY BARRIER AT NO COST TO THE DEPARTMENT UNLESS OTHERWISE STATED IN THE TRANSPORTATION MANAGEMENT PLANS, TEMPORARY BARRIER IS PROTECTING A HAZARD, OR AS DIRECTED BY THE ENGINEER.

INSTALL TEMPORARY BARRIER WITH THE TRAFFIC FLOW BEGINNING WITH THE UPSTREAM SIDE OF TRAFFIC. REMOVE TEMPORARY BARRIER AGAINST THE TRAFFIC FLOW BEGINNING WITH THE DOWNSTREAM SIDE OF TRAFFIC.

INSTALL AND SPACE DRUMS NO GREATER THAN TWICE THE POSTED SPEED LIMIT (MPH) TO CLOSE OR KEEP THE SECTION OF THE ROADWAY CLOSED UNTIL THE TEMPORARY BARRIER CAN BE PLACED OR AFTER THE TEMPORARY BARRIER IS REMOVED.

M. PROTECT THE APPROACH END OF MOVABLE/PORTABLE CONCRETE BARRIER AT ALL TIMES DURING THE INSTALLATION AND REMOVAL OF THE BARRIER BY EITHER A TRUCK MOUNTED ATTENUATOR (MAXIMUM 72 HOURS) OR A TEMPORARY CRASH CUSHION.

PROTECT THE APPROACH END OF MOVABLE/PORTABLE CONCRETE BARRIER FROM ONCOMING TRAFFIC AT ALL TIMES BY A TEMPORARY CRASH CUSHION UNLESS THE APPROACH END OF MOVABLE/PORTABLE CONCRETE BARRIER IS OFFSET FROM ONCOMING TRAFFIC AS FOLLOWS OR AS SHOWN IN THE PLANS: (SEE ALSO 1101.05)

POSTED SPEED LIMIT	MINIMUM OFFSET
40 OR LESS	15 FT
45-50	20 FT
55	25 FT
60 MPH OR GREATER	30 FT

TRAFFIC CONTROL DEVICES

N. WHEN LANE CLOSURES ARE NOT IN EFFECT SPACE CHANNELIZING DEVICES IN WORK AREAS NO GREATER IN FEET THAN TWICE THE POSTED SPEED LIMIT (MPH) EXCEPT 10 FT ON-CENTER IN RADII, AND 3 FT OFF THE EDGE OF AN OPEN TRAVELWAY. REFER TO STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES SECTIONS 1130 (DRUMS), 1135 (CONES) AND 1180 (SKINNY DRUMS) FOR ADDITIONAL REQUIREMENTS.

O. PLACE TYPE III BARRICADES, WITH "ROAD CLOSED" SIGN R11-2 ATTACHED, OF SUFFICIENT LENGTH TO CLOSE ENTIRE ROADWAY.

PAVEMENT MARKINGS AND MARKERS

P. INSTALL TEMPORARY PAVEMENT MARKINGS AND TEMPORARY PAVEMENT MARKERS ON INTERIM LAYERS OF PAVEMENT AS FOLLOWS:

ROAD NAME	MARKING	MARKER
SR 1001 ELLIJAY RD.	PAINT	NONE

Q. PLACE ONE APPLICATION OF PAINT FOR TEMPORARY TRAFFIC PATTERNS. PLACE A SECOND APPLICATION OF PAINT SIX (6) MONTHS AFTER THE INITIAL APPLICATION AND EVERY SIX MONTHS AS DIRECTED BY THE ENGINEER.

R. TIE PROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING LINES.

S. REMOVE/REPLACE ANY CONFLICTING/DAMAGED PAVEMENT MARKINGS AND MARKERS BY THE END OF EACH DAY'S OPERATION.

MISCELLANEOUS

T. IN THE EVENT A TIE-IN CANNOT BE MADE IN ONE DAY'S TIME, BRING THE TIE-IN AREA TO AN APPROPRIATE ROADWAY ELEVATION AS DETERMINED BY THE ENGINEER. PLACE BLACK ON ORANGE "LOOSE GRAVEL" SIGNS (W8-7) AND BLACK ON ORANGE "PAVEMENT ENDS" SIGNS (W8-3) 500 FT AND 500 FT RESPECTIVELY IN ADVANCE OF THE UNEVEN AREAS. USE DRUMS TO DELINEATE THE EDGE OF ROADWAY ALONG UNPAVED AREAS.

LOCAL NOTES

CONTRACTOR TO MAINTAIN DRIVEWAY ACCESS AT ALL TIMES

APPROVED: _____ DATE: 10/16/13

NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. YOBO

DIVISION OF HIGHWAYS * STATE OF NORTH CAROLINA * DEPARTMENT OF TRANSPORTATION * WORK ZONE TRAFFIC CONTROL

TRANSPORTATION OPERATIONS PLAN

Mattern & Craig
CONSULTING ENGINEERS * SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

PROJECT REFERENCE NO.	SHEET
17BP.14.R.68	TMP-1C

GEOTECHNICAL ENGINEER — SIGNATURE — DATE

ENGINEER — NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. VOSO — SIGNATURE — DATE 10/16/13

GROUNDWATER CONDITION (SEE NOTE 6)	H SHORING HEIGHT (FT)	SLOPE OR SURCHARGE CASE WITH NO TRAFFIC IMPACT					SURCHARGE CASE WITH TRAFFIC IMPACT				
		SHEET PILES		H-PILES WITH TIMBER LAGGING			SHEET PILES		H-PILES WITH TIMBER LAGGING		
		MINIMUM REQUIRED EMBEDMENT (FT)	MINIMUM REQUIRED SECTION MODULUS (IN^3/FT)	MINIMUM REQUIRED EMBEDMENT* (FT) (SEE NOTE 10)			MINIMUM REQUIRED EMBEDMENT (FT)	MINIMUM REQUIRED SECTION MODULUS (IN^3/FT)	MINIMUM REQUIRED EMBEDMENT* (FT) (SEE NOTE 10)		
				HP 10x42	HP 12x53	HP 14x73			HP 10x42	HP 12x53	HP 14x73
GROUNDWATER ELEVATION BEWTEEN BOTTOM OF SHORING AND PILE TIP	< 6	11.5	4.5	11.5	11.5	11.5	16.0	12.0	13.0	13.0	13.0
	7	13.0	7.0	13.0	13.0	13.0	17.0	14.5	14.5	14.5	14.5
	8	15.0	10.0	--	15.0	15.0	18.0	17.0	--	15.5	15.5
	9	17.0	14.0	--	17.0	17.0	19.0	20.0	--	17.0	17.0
	10	18.5	19.5	--	--	18.5	20.0	23.5	--	--	18.5
	11	20.5	26.0	--	--	--	21.0	28.0	--	--	20.0
	12	22.5	33.0	--	--	--	22.0	33.0	--	--	21.5
GROUNDWATER ELEVATION BELOW PILE TIP	< 6	7.5	3.0	8.0	8.0	8.0	11.0	10.0	9.5	9.5	9.5
	7	8.5	4.5	9.5	9.5	9.5	12.0	12.0	10.5	10.5	10.5
	8	10.0	6.5	10.5	10.5	10.5	12.5	14.0	11.5	11.5	11.5
	9	11.0	9.5	--	12.0	12.0	13.5	16.5	--	12.5	12.5
	10	12.5	13.0	--	--	13.5	14.0	19.5	--	13.5	13.5
	11	13.5	17.0	--	--	14.5	15.0	22.5	--	--	14.5
	12	15.0	21.5	--	--	16.0	16.0	25.5	--	--	15.5

MINIMUM REQUIRED EMBEDMENT AND SECTION MODULUS

*DO NOT USE H-PILES WITH TIMBER LAGGING FOR GROUNDWATER CONDITION, SHORING HEIGHT AND H-PILE SIZE SHOWN IF MINIMUM REQUIRED EMBEDMENT IS "--".

NOTES:

1. AT THE CONTRACTOR'S OPTION, USE STANDARD TEMPORARY SHORING AS NOTED IN THE PLANS.
2. FOR STANDARD TEMPORARY SHORING, SEE STANDARD SHORING PROVISION.
3. STANDARD TEMPORARY SHORING IS BASED ON THE FOLLOWING IN-SITU ASSUMED SOIL PARAMETERS:
   UNIT WEIGHT, γ = 120 LB/CF
   FRICTION ANGLE, ϕ = 30 DEGREES
   COHESION, c = 0 LB/SF
4. DO NOT USE STANDARD TEMPORARY SHORING IF ASSUMED SOIL PARAMETERS ARE NOT APPLICABLE.
5. DO NOT USE STANDARD TEMPORARY SHORING WHEN VERY LOOSE OR SOFT SOIL OR MUCK IS WITHIN THE EMBEDMENT DEPTH.
6. USE GROUNDWATER ELEVATION NOTED IN THE PLANS. IF NO GROUNDWATER ELEVATION IS SHOWN IN THE PLANS, USE "GROUNDWATER ELEVATION BETWEEN BOTTOM OF SHORING AND PILE TIP" FOR GROUNDWATER CONDITION. DO NOT USE STANDARD TEMPORARY SHORING IF GROUNDWATER IS ABOVE BOTTOM OF SHORING.
7. AT THE CONTRACTOR'S OPTION OR IF AVAILABLE CLEAR DISTANCE IS LESS THAN THE MINIMUM REQUIRED FOR CONCRETE BARRIER, SET BARRIER NEXT TO AND UP AGAINST TRAFFIC SIDE OF PILES AND USE "SURCHARGE CASE WITH TRAFFIC IMPACT".
8. AT THE CONTRACTOR'S OPTION OR IF AVAILABLE CLEAR DISTANCE IS LESS THAN 4' FOR TEMPORARY GUARDRAIL, ATTACH GUARDRAIL TO TRAFFIC SIDE OF PILES AS SHOWN IN THE PLANS AND USE "SURCHARGE CASE WITH TRAFFIC IMPACT".
9. MINIMUM REQUIRED EXTENSION IS 6" FOR "SLOPE OR SURCHARGE CASE WITH NO TRAFFIC IMPACT" AND 32" FOR "SURCHARGE CASE WITH TRAFFIC IMPACT".
10. MINIMUM REQUIRED EMBEDMENT FOR H-PILES WITH TIMBER LAGGING IS BASED ON DRIVEN H-PILES AT MAXIMUM 6' SPACING. AT THE CONTRACTOR'S OPTION, EMBEDMENT DEPTHS MAY BE REDUCED BY 25% FOR DRILLED-IN H-PILES.
11. SUBMIT A "STANDARD TEMPORARY SHORING SELECTION FORM" AT LEAST 7 DAYS BEFORE STARTING TEMPORARY SHORING CONSTRUCTION. UP TO 3 SHORING LOCATIONS MAY BE INCLUDED ON EACH FORM.
12. CONTACT THE ENGINEER IF PILES DO NOT ATTAIN THE MINIMUM REQUIRED EMBEDMENT.



CONCRETE BARRIER

**TOP OF SHORING = EDGE OF PAVEMENT



TEMPORARY GUARDRAIL

**GUARDRAIL FACE = EDGE OF PAVEMENT



STANDARD TEMPORARY SHORING

(SLOPE CASE)
*SEE TABLE ABOVE.

STANDARD TEMPORARY SHORING

(SURCHARGE CASE)
*SEE TABLE ABOVE.

GEOTECHNICAL ENGINEERING UNIT
STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

STANDARD DRAWING NO. 1801.01

STANDARD TEMPORARY SHORING

DATE: 1-17-12

PROJ. REFERENCE NO.	SHEET NO.
17BP.14.R.68	TMP-2

PHASE I OVERVIEW

PHASE I

USING ROADWAY STANDARD DRAWING 1101.02, SHEET 1 OF 15, COMPLETE THE FOLLOWING WORKING IN A CONTINUOUS MANNER, AS SHOWN, USING FLAGGERS, FLAGGER AHEAD SIGNS AND DRUMS.

STEP 1: - INSTALL ADVANCE WARNING SIGNS, WORK ZONE TRAFFIC CONTROL SIGNS, AND TEMPORARY SIGNAL, KEEPING SIGNS AND SIGNAL HEADS COVERED UNTIL THE DAY WORK BEGINS.

STEP 2: - PLACE TEMPORARY PAVEMENT MARKING (PAINT).

- UNCOVER ALL WARNING AND WORK ZONE TRAFFIC CONTROL SIGNS AND AND SIGNALS, PLACE SR 1001 (ELLIJAY RD.) TRAFFIC IN A ONE-LANE, TWO-WAY PATTERN FROM -L- STA. 9+50+/- TO -L- STA. 15+30+/-.

USING ROADWAY STANDARD DRAWING 1101.02, SHEET 1 OF 15, COMPLETE THE FOLLOWING WORKING IN A CONTINUOUS MANNER, AS SHOWN, USING TEMPORARY SIGNALS, WORK ZONE TRAFFIC CONTROL SIGNS AND DRUMS.

STEP 3: - PLACE TEMPORARY CONCRETE BARRIER FROM -L- STA. 12+88 TO -L- STA. 13+28, KEEPING ENDS PROTECTED BY TEMPORARY CRASH CUSHIONS. BARRIER SHALL BE TEMPORARY METAL RAIL ACROSS EXISTING BRIDGE FROM -L- STA. 12+97 TO -L- STA. 13+18 (SEE STRUCTURE PLANS, S-3).

- REMOVE A PORTION OF THE BRIDGE AND BEAMS ON THE SOUTHERN SIDE AS NOTED ON BRIDGE STAGE 1 CONSTRUCTION SHEET S-3.

STEP 4: - USING GEOTECHNICAL STANDARD DRAWING 1801.01, OR CONTRACTOR PROVIDED DESIGN, PLACE TEMPORARY SHORING BEHIND CONCRETE BARRIER AT THE FOLLOWING LOCATIONS:
-L- STA. 12+88, 2.60' LT. TO -L- STA. 12+98, 2.60' LT.
-L- STA. 13+18, 2.60' LT. TO -L- STA. 13+28, 2.60' LT.

STEP 5: - BEHIND TEMPORARY BARRIER, BEGIN CONSTRUCTION OF PROPOSED STRUCTURE RIGHT OF -L- FROM -L- STA. 12+92.80 TO -L- STA. 13+22.80, AS SHOWN (SEE STRUCTURE PLANS).

STEP 6: - CONSTRUCT RIGHT OF -L- ALL PROPOSED ROADWAY AS SHOWN AND PROPOSED STRUCTURE UP TO BUT NOT INCLUDING THE FINAL LAYER OF SURFACE COURSE, FROM -L- STA. 10+50 TO -L- STA. 15+80 (SEE ROADWAY PLANS).

STEP 7: - CONSTRUCT ALL GUARDRAIL RIGHT OF -L-.



LEGEND

PROPOSED CONSTRUCTION

NOTES: 1. TEMPORARY SIGNALS SHALL BE PLACED 40' FROM LOCATION OF TEMPORARY STOPBAR.
2. BARRELS SHALL BE SPACED AT 20' TYPICALLY.

Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

APPROVED: _____ DATE: 10/16/13

NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. VOSO

DIVISION OF HIGHWAYS * STATE OF NORTH CAROLINA * DEPARTMENT OF TRANSPORTATION * WORK ZONE TRAFFIC CONTROL

TRANSPORTATION MANAGEMENT PLAN PHASE I

8:27:34 AM
R:\3215\Bridge0081\Traffic\TrafficControl\Roadway\17BP14R68_TC_TMP2.dgn
bgross

PHASE II OVERVIEW

PHASE II

USING ROADWAY STANDARD DRAWING 1101.02, SHEET 1 OF 15, COMPLETE THE FOLLOWING WORKING IN A CONTINUOUS MANNER, AS SHOWN, USING TEMPORARY SIGNALS, WORK ZONE TRAFFIC CONTROL SIGNS AND DRUMS.

STEP 1: - REMOVE PHASE I PAVEMENT MARKINGS AND RESTRIPE (PAINT) AS SHOWN.

STEP 2: - RESET TEMPORARY BARRIER FROM -L- STA. 12+83 TO -L- STA. 13+33, KEEPING ENDS PROTECTED BY TEMPORARY CRASH CUSHIONS. BARRIER SHALL BE TEMPORARY METAL RAIL ACROSS BRIDGE FROM -L- STA. 12+92.80 TO -L- STA. 13+22.80 (SEE STRUCTURE PLANS, SHEET S-3).

- REMOVE REMAINING PORTION OF BRIDGE AND BEAMS AS NOTED ON BRIDGE STAGE 2 CONSTRUCTION (SEE STRUCTURE PLANS, SHEET S-3).

STEP 3: - BEHIND TEMPORARY BARRIER, BEGIN CONSTRUCTION OF PROPOSED STRUCTURE LEFT OF -L- FROM -L- STA. 12+92.80 TO -L- STA. 13+22.80, AS SHOWN (SEE STRUCTURE PLANS).

STEP 4: - CONSTRUCT LEFT OF -L- ALL PROPOSED ROADWAY, PROPOSED STRUCTURE, AND PROPOSED GUARDRAIL UP TO BUT NOT INCLUDING THE FINAL LAYER OF SURFACE COURSE, FROM -L- STA. 10+50 TO -L- STA. 14+30 (SEE ROADWAY PLANS).

- TEMPORARY SHORING MAY BE REMOVED AS WORK ALLOWS.

PHASE III

USING ROADWAY STANDARD DRAWING 1101.02, SHEET 1 OF 15, COMPLETE THE FOLLOWING WORKING IN A CONTINUOUS MANNER, AS SHOWN, USING FLAGGERS, FLAGGER AHEAD SIGNS AND DRUMS.

STEP 1: - REMOVE TEMPORARY SIGNALS, STOP HERE ON RED SIGNS, SIGNAL AHEAD SIGNS, EDGELINE AND STOP BARS. UTILIZE FLAGGERS TO MAINTAIN ONE-LANE, TWO-WAY TRAFFIC FROM -L- STA. 14+30 TO -L- STA. 15+80.

STEP 2: - CONSTRUCT ALL PROPOSED ROADWAY FROM -L- STA. 14+30 TO -L- STA. 15+80, UP TO BUT NOT INCLUDING THE FINAL SURFACE COURSE. CONSTRUCT PROPOSED DRIVEWAY TIE AT STA. 15+70+/-.

STEP 3: - PLACE THE FINAL LAYER OF SURFACE COURSE , FINAL MARKINGS (PAINT) IN THE FINAL PATTERN, AND OPEN -L-, SR 1001 (ELLIJAY RD.) TO THE FINAL TWO-LANE, TWO-WAY PATTERN (SEE ROADWAY PLANS). MAINTAIN ONE-LANE, TWO-WAY TRAFFIC AT ALL TIMES.

STEP 4: - REMOVE ALL TRAFFIC CONTROL DEVICES.



NOTES: 1. TEMPORARY SIGNALS SHALL BE PLACED 40' FROM LOCATION OF TEMPORARY STOPBAR.
2. BARRELS SHALL BE SPACED AT 20' TYPICALLY.

LEGEND

PROPOSED CONSTRUCTION

Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

APPROVED: [signature] DATE: 10/16/13

NORTH CAROLINA PROFESSIONAL ENGINEER SEAL 022599 JAMES B. VOSO

DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION WORK ZONE TRAFFIC CONTROL

TRANSPORTATION MANAGEMENT PLAN PHASE II/III

8:30:26 AM
R:\3215\Bridge008\Traffic\TrafficControl\Roadway\17BP14R68_TC_TMP3.dgn
bgross

PROJ. REFERENCE NO.	SHEET NO.
17BP.14.R.68	PMP-1



NOTE: RESET EXISTING STOP SIGN ON LITTLE ELIJAY ROAD WHEN CONSTRUCTION IS COMPLETE.

FINAL 4" PAVEMENT MARKINGS TO RECEIVE DOUBLE COATING

LEGEND

PA WHITE EDGELINE
PI YELLOW DOUBLE CENTER

PROJECT MARKING SCHEDULE
BRIDGE 008

SYMBOL	DESCRIPTION	PAY ITEM	PAY ITEM QUANTITY
PI	YELLOW DOUBLE CENTER	PAINT 4" (DOUBLE COAT)	2120 LF
PA	WHITE EDGELINE	PAINT 4" (DOUBLE COAT)	2140 LF

GRAPHIC SCALE
25' 0' 25' 50'
100'
PLANS

Mattern & Craig
SINCE 1978
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

APPROVED: _____ DATE: 10/16/13

NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. VOSO

DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
WORK ZONE TRAFFIC CONTROL

PAVEMENT MARKING PLAN

H6:48 PM
R:\325\Bridge008\Traffic\TrafficControl\Roadway\17BP14R68_TC_PMP1.dgn
Dgross

PROJECT NO: 17BP.14.R.68

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.14.R.68	EC-1	

STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

PLAN FOR PROPOSED
HIGHWAY EROSION CONTROL



MACON COUNTY

LOCATION: BRIDGE 008 OVER BERRY PRONG ELLIJAY CREEK ON SR 1001 (ELLIJAY ROAD)

TYPE OF WORK: GRADING, DRAINAGE, PAVING, & STRUCTURE

STA. 10+50.00 -L- BEGIN TIP PROJECT 17BP.14.R.68



STA. 15+80.00 -L- END TIP PROJECT 17BP.14.R.68

DANA BOLDEN
LEVEL IIIA NAME
3171
LEVEL IIIA CERTIFICATION NO.

CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II

EROSION AND SEDIMENT CONTROL MEASURES

Std. #	Description	Symbol
1630.03	Temporary Silt Ditch	
1630.05	Temporary Diversion	
1605.01	Temporary Silt Fence	
1606.01	Special Sediment Control Fence	
1622.01	Temporary Berms and Slope Drains	
1630.02	Silt Basin Type B	
1633.01	Temporary Rock Silt Check Type-A	
	Temporary Rock Silt Check Type-A with Matting and Polyacrylamide (PAM)	
1633.02	Temporary Rock Silt Check Type-B	
	Wattle/Coir Fiber Wattle	
	Wattle/Coir Fiber Wattle with Polyacrylamide (PAM)	
1634.01	Temporary Rock Sediment Dam Type-A	
1634.02	Temporary Rock Sediment Dam Type-B	
1635.01	Rock Pipe Inlet Sediment Trap Type-A	
1635.02	Rock Pipe Inlet Sediment Trap Type-B	
1630.04	Stilling Basin	
1630.06	Special Stilling Basin	
	Rock Inlet Sediment Trap:	
1632.01	Type A	A
1632.02	Type B	B
1632.03	Type C	C
	Skimmer Basin	
	Tiered Skimmer Basin	
	Infiltration Basin	

THIS PROJECT CONTAINS EROSION CONTROL PLANS FOR CLEARING AND GRUBBING PHASE OF CONSTRUCTION.

THIS PROJECT HAS BEEN DESIGNED TO SENSITIVE WATERSHED STANDARDS.

ENVIRONMENTALLY SENSITIVE AREA(S) EXIST ON THIS PROJECT

Refer To E. C. Special Provisions for Special Considerations.

GRAPHIC SCALE

0 50

PLANS

ROADSIDE ENVIRONMENTAL UNIT
DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA

THESE EROSION AND SEDIMENT CONTROL PLANS COMPLY WITH THE REGULATIONS SET FORTH BY THE NCG-010000 GENERAL CONSTRUCTION PERMIT EFFECTIVE AUGUST 3, 2011 ISSUED BY THE NORTH CAROLINA DEPARTMENT OF ENVIRONMENT AND NATURAL RESOURCES DIVISION OF WATER QUALITY.

Prepared In the Office of:

Mattern & Craig
SINCE 1978
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

Reviewed In the Office of:

ROADSIDE ENVIRONMENTAL UNIT
1 South Wilmington St.
Raleigh, NC 27611

2012 STANDARD SPECIFICATIONS

Roadway Standard Drawings

The following roadway english standards as appear in "Roadway Standard Drawings"- Roadway Design Unit - N. C. Department of Transportation - Raleigh, N. C., dated January 2012 and the latest revison thereto are applicable to this project and by reference hereby are considered a part of these plans.

1604.01 Railroad Erosion Control Detail
1605.01 Temporary Silt Fence
1606.01 Special Sediment Control Fence
1607.01 Gravel Construction Entrance
1622.01 Temporary Berms and Slope Drains
1630.01 Riser Basin
1630.02 Silt Basin Type B
1630.03 Temporary Silt Ditch
1630.04 Stilling Basin
1630.05 Temporary Diversion
1630.06 Special Stilling Basin
1631.01 Matting Installation
1632.01 Rock Inlet Sediment Trap Type A
1632.02 Rock Inlet Sediment Trap Type B
1632.03 Rock Inlet Sediment Trap Type C
1633.01 Temporary Rock Silt Check Type A
1633.02 Temporary Rock Silt Check Type B
1634.01 Temporary Rock Sediment Dam Type A
1634.02 Temporary Rock Sediment Dam Type B
1635.01 Rock Pipe Inlet Sediment Trap Type A
1635.02 Rock Pipe Inlet Sediment Trap Type B
1640.01 Coir Fiber Baffle
1645.01 Temporary Stream Crossing

1:00:34 PM
215\Bridge008\Environmental\Design\17BP14R68_EC_TSH.dgn
bgross

PROJECT REFERENCE NO.	SHEET NO.
1717.BP.14.R.68	EC-2
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

COIR FIBER WATTLE DETAIL



ISOMETRIC VIEW



CROSS SECTION VEE DITCH



CROSS SECTION TRAPEZOIDAL DITCH

NOTES:

USE MINIMUM 12 IN. DIAMETER COIR FIBER (COCONUT FIBER) WATTLE.

USE 2 FT. WOODEN STAKES WITH A 2 IN. BY 2 IN. NOMINAL CROSS SECTION.

ONLY INSTALL WATTLE(S) TO A HEIGHT IN DITCH SO FLOW WILL NOT WASH AROUND WATTLE AND SCOUR DITCH SLOPES AND AS DIRECTED.

INSTALL A MINIMUM OF 2 UPSLOPE STAKES AND 4 DOWNSLOPE STAKES AT AN ANGLE TO WEDGE WATTLE TO BOTTOM OF DITCH.

PROVIDE STAPLES MADE OF 0.125 IN. DIAMETER STEEL WIRE FORMED INTO A U SHAPE NOT LESS THAN 12" IN LENGTH.

INSTALL STAPLES APPROXIMATELY EVERY 1 LINEAR FOOT ON BOTH SIDES OF WATTLE AND AT EACH END TO SECURE IT TO THE SOIL.

INSTALL MATTING IN ACCORDANCE WITH SECTION 1631 OF THE STANDARD SPECIFICATIONS.



INSET A



INSET B



TOP VIEW

PROJECT REFERENCE NO.	SHEET NO.
17BRPJ4,R.68	EC-3

ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
	NORTH CAROLINA PROFESSIONAL SEAL 028945 ENGINEER DANA J. BOLDEN

DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA

SOIL STABILIZATION TIMEFRAMES

SITE DESCRIPTION	STABILIZATION TIME	TIMEFRAME EXCEPTIONS
PERIMETER DIKES, SWALES, DITCHES AND SLOPES	7 DAYS	NONE
HIGH QUALITY WATER (HQW) ZONES	7 DAYS	NONE
SLOPES STEEPER THAN 3:1	7 DAYS	IF SLOPES ARE 10' OR LESS IN LENGTH AND ARE NOT STEEPER THAN 2:1, 14 DAYS ARE ALLOWED.
SLOPES 3:1 OR FLATTER	14 DAYS	7 DAYS FOR SLOPES GREATER THAN 50' IN LENGTH.
ALL OTHER AREAS WITH SLOPES FLATTER THAN 4:1	14 DAYS	NONE, EXCEPT FOR PERIMETERS AND HQW ZONES.

PROJECT REFERENCE NO.	SHEET NO.
17BPJ4.R.68	EC-3A

ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
	NORTH CAROLINA PROFESSIONAL SEAL 028945 ENGINEER DANA J. BOLDEN 10/16/13

DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA

SOIL STABILIZATION SUMMARY SHEET

MATTING FOR EROSION CONTROL

CONST SHEET NO.	LINE	FROM STATION	TO STATION	SIDE	ESTIMATE (SY)
				SUBTOTAL	0
MISCELLANEOUS MATTING TO BE INSTALLED AS DIRECTED BY THE ENGINEER					2200
				TOTAL	2200
				SAY	2200

PERMANENT SOIL REINFORCEMENT MAT

CONST SHEET NO.	LINE	FROM STATION	TO STATION	SIDE	ESTIMATE (SY)
				SUBTOTAL	0
		ADDITIONAL PSRM TO BE INSTALLED			0
				TOTAL	0
				SAY	0

PROJECT REFERENCE NO.	SHEET NO.
17BPJ4.R.68	EC-4/CONST.4
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

NAD 83/
NSRS 2007



CLEARING AND GRUBBING
EROSION CONTROL FOR
CONSTRUCTION SHEET 4

NOTES: ANY DEVIATION FROM OPTIONS GIVEN WILL REQUIRE PRIOR APPROVAL BY ENGINEER.

ADDITIONAL EROSION CONTROL DEVICES MAY NEED TO BE INSTALLED AS DIRECTED BY THE ENGINEER.

IF ANY PUMPED DEWATERING IS REQUIRED, A SPECIAL STILLING BASIN SHALL BE PROVIDED AS NEEDED

NOTE:

PLACE TEMPORARY ROCK SILT CHECKS TYPE – A AT DRAINAGE OUTLETS.

DETAIL 1
SPECIAL CUT DITCH
(Not to Scale)



FROM STA. 11+00 TO STA. 12+95 RT

CLEAN WATER DIVERSION
→ → CWD → → CWD → → CWD → → CWD → →
(Not to Scale)



ENVIRONMENTALLY SENSITIVE AREA
SEE PROJECT SPECIAL PROVISIONS

PROJECT REFERENCE NO.	SHEET NO.
17BPJ4.R.68	EC-5/CONST.4
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

NAD 83/
NSRS 2007

0.230 ACRE STREAMBANK REFORESTATION



SEE RF-1, RF-2, AND PROJECT SPECIAL PROVISIONS

Place Matting for Erosion Control on Slope as Work Allows.

NOTES: ANY DEVIATION FROM OPTIONS GIVEN WILL REQUIRE PRIOR APPROVAL BY ENGINEER.

ADDITIONAL EROSION CONTROL DEVICES MAY NEED TO BE INSTALLED AS DIRECTED BY THE ENGINEER.

IF ANY PUMPED DEWATERING IS REQUIRED, A SPECIAL STILLING BASIN SHALL BE PROVIDED AS NEEDED

NOTE:
PLACE TEMPORARY ROCK SILT CHECKS TYPE – A AT DRAINAGE OUTLETS.

NOTE:
UTILIZE TEMPORARY SILT CHECK TYPE – A AS STILLING BASIN WHERE APPLICABLE.



DETAIL 1
SPECIAL CUT DITCH
(Not to Scale)



FROM STA. 11+00 TO STA. 12+95 RT

CLEAN WATER DIVERSION
→→ CWD →→ CWD →→ CWD →→ CWD →→
(Not to Scale)



PLANTING DETAILS

LIVE STAKES PLANTING DETAIL

LIVE STAKE





BANK STABILIZATION WITH LIVE STAKES

NOTE:
LIVE STAKES SHALL BE SPACED APPROXIMATELY 4 FEET ON CENTER
LIVE STAKES SHALL BE DRIVEN UNTIL APPROXIMATELY 3/4 OF LIVE STAKE IS WITHIN GROUND

BAREROOT PLANTING DETAIL
DIBBLE PLANTING METHOD
USING THE KBC PLANTING BAR



1. Insert planting bar as shown and pull handle toward planter.
2. Remove planting bar and place seedling at correct depth.
3. Insert planting bar 2 inches toward planter from seedling.



4. Pull handle of bar toward planter, firming soil at bottom.
5. Push handle forward firming soil at top.
6. Leave compaction hole open. Water thoroughly.

PLANTING NOTES:

PLANTING BAG
During planting, seedlings shall be kept in a moist canvas bag or similar container to prevent the root systems from drying.

KBC PLANTING BAR
Planting bar shall have a blade with a triangular cross section, and shall be 12 inches long, 4 inches wide and 1 inch thick at center.

ROOT PRUNING
All seedlings shall be root pruned, if necessary, so that no roots extend more than 10 inches below the root collar.

☐ TYPE 1 STREAMBANK REFORESTATION SHALL BE PLANTED 3 FT. TO 5 FT. ON CENTER, RANDOM SPACING, AVERAGING 4 FT. ON CENTER, APPROXIMATELY 2724 PLANTS PER ACRE.

☐ TYPE 2 STREAMBANK REFORESTATION SHALL BE PLANTED 6 FT. TO 10 FT. ON CENTER, RANDOM SPACING, AVERAGING 8 FT. ON CENTER, APPROXIMATELY 680 PLANTS PER ACRE.

☐ NOTE: TYPE 1 AND TYPE 2 STREAMBANK REFORESTATION SHALL BE PAID FOR AS "STREAMBANK REFORESTATION"

STREAMBANK REFORESTATION TYPICAL



STREAMBANK REFORESTATION

MIXTURE, TYPE, SIZE, AND FURNISH SHALL CONFORM TO THE FOLLOWING:

TYPE 1			
50%	SALIX NIGRA	BLACK WILLOW	2 ft – 3 ft LIVE STAKES
50%	CORNUS AMOMUM	SILKY DOGWOOD	2 ft – 3 ft LIVE STAKES
TYPE 2			
25%	LIRIODENDRON TULIPIFERA	TULIP POPLAR	12 in – 18 in BR
25%	PLATANUS OCCIDENTALIS	SYCAMORE	12 in – 18 in BR
25%	PRUNUS SEROTINA	BLACK CHERRY	12 in – 18 in BR
25%	BETULA NIGRA	RIVER BIRCH	12 in – 18 in BR

☐ SEE PLAN SHEETS FOR AREAS TO BE PLANTED

PROJECT REFERENCE NO.	SHEET NO.
17.BPJ4.R.68	RF-1
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. VOSO

STREAMBANK REFORESTATION
DETAIL SHEET 1 OF 2

N.C.D.O.T. - ROADSIDE ENVIRONMENTAL UNIT

PROJECT REFERENCE NO.	SHEET NO.
17BPJ4.R.68	RF-2
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 022598 ENGINEER JAMES B. VOSO



PLAN VIEW



TYPICAL CROSS SECTION



ANCHOR OPTIONS

COIR FIBER MATTING DETAIL

NOT TO SCALE

STREAMBANK REFORESTATION
DETAIL SHEET 2 OF 2
N.C.D.O.T. - ROADSIDE ENVIRONMENTAL UNIT

5/14/99

UTILITIES BY OTHERS
BRIDGE: 008

NOTE:
ALL PROPOSED UTILITY WORK SHOWN ON THIS SHEET WILL BE DONE BY OTHERS

PROJECT REFERENCE NO.	SHEET NO.
17BPJ4.R.68	UBO-1
R/W SHEET NO.	

ROADWAY DESIGN ENGINEER — NORTH CAROLINA PROFESSIONAL SEAL 022599 ENGINEER JAMES B. VOSO

HYDRAULICS ENGINEER — NORTH CAROLINA PROFESSIONAL SEAL 028945 ENGINEER DANA J. BOLDEN

Prepared in the Office of:
Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

50 25 0 50 100
SCALE

RETAINED

EST 125 CY EXCAVATION
EST 150 TON CLASS II RIP RAP
(STRUCTURES PAY ITEMS)

TEMPORARY POLE DURING BRIDGE CONSTRUCTION

TEMPORARY LINE DURING BRIDGE CONSTRUCTION

RESET FENCE TO R/W OR EDGE OF STREAM

EXIST U/G TELE ABANDONED IN PLACE

TEMPORARY LINE DURING BRIDGE CONSTRUCTION

SPLICE POINT AT EXISTING PEDESTAL

① DENNIS L. GRIMES DB E-30 PG 171

RESET FENCE TO R/W

RETAINED

② DENNIS SHEPARD DB I-25 PG 74

PROP PEDESTAL

RETAINED

RETAIN

EX BURIED CABLE DUG UP AND SWING INTO NEW PEDESTAL

③ ELLIJAY MISSIONARY BAPT CHURCH DB V-II PG 232

EX POLE TO BE REMOVED AND REPALCED WITH A NEW PEDESTAL

END TIP PROJECT 17BPJ4.R.68
-L- POT STA 15+80.00

EX FIBER PEDESTAL

REMOVED DURING CONSTRUCTION. WHEN BRIDGE CONSTRUCTION COMPLETED WILL INSTALL LINE BACK TO ORGINAL ROUTE

RETAINED

RETAINED

TEMPORARY LINE DURING BRIDGE CONSTRUCTION

⑥ ROBERT B. MILTON DB I-22 PG 799

BEGIN TIP PROJECT 17BPJ4.R.68
-L- POT STA 10+50.00

REMOVED DURING CONSTRUCTION. WHEN BRIDGE CONSTRUCTION COMPLETED WILL INSTALL LINE BACK TO ORGINAL ROUTE

SPECIAL CUT DITCH SEE DETAIL #1

⑤ ROLAND F. RIVERO DB R-17 PG 480

TEMPORARY LINE & POLES DURING BRIDGE CONSTRUCTION

BEGIN BRIDGE
-L- POT STA 12+92.80

REPLACED

REMOVED

BM #1
-BL- STA 7+67.91
48.40' RT
ELEV=2205.51'

CHANNEL CHANGE
SEE STREAM RELOCATION PLANS

④ ROLAND F. RIVERO DB R-17 PG 482

END BRIDGE
-L- POT STA 13+22.80

RETAINED

RETAINED

NAD 83/
NSRS 2007

R:\3215\B-Page2026\Utilities\17BPJ4R68_UBO_PSH.dgn
12:41:25 PM

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

CROSS SECTION SUMMARY

LOCATION	UNCLASSIFIED EXCAVATION	EMBT+%
-L- 10+50 TO 11+00	0	17
-L- 11+00 TO 11+50	18	39
-L- 11+50 TO 12+00	468	37
-L- 12+00 TO 12+50	728	25
-L- 12+50 TO 13+00	361	10
-L- 13+00 TO 13+50	119	83
-L- 13+50 TO 14+00	16	171
-L- 14+00 TO 14+50	0	129
-L- 14+50 TO 15+00	10	65
-L- 15+00 TO 15+50	0	30
-L- 15+50 TO 15+80	0	4

Note: Embankment column does not include fill for undercut.

Approximate quantities only. Unclassified excavation, borrow excavation, shoulder borrow, fine grading, clearing and grubbing, breaking of existing pavement and removal of existing pavement will be paid for at the lump sum price for "Grading".

8/23/99

0 5 10	PROJ. REFERENCE NO.	SHEET NO.
	17BP.14.R.68	X-1

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

2250
2240
2230
2220
2210
2200
2190

10+50.00

10+00.00

—/—

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

10:05:47 AM
\\192.168.13.10\projects\3215\Bridge008\Roadway\XSC\17BP14R68_RDY_XPL.dgn
bargess

8/23/99

10:15:27 AM
\\192.168.13.10\projects\3215\Bridge008\Roadway\XSC\17BP14R68_RDY_XPL.dgn
bgross

8/23/99

0 5 10	PROJ. REFERENCE NO.	SHEET NO.
	17BP.14.R.68	X-3



10:20:30 AM
\\192.168.13.10\projects\3215\Bridge008\Roadway\XSC\17BP14R68_RDY_XPL.dgn
bgross

8/23/99

0 5 10	PROJ. REFERENCE NO.	SHEET NO.
	17BP.14.R.68	X-4

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

2220
2210
2200

16+00.00

S.S. 2207.32 ℄ 0.046 0.006 ℄ S.S. 2207.22

2206.17 2208.2

15+50.00

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

10:55:15 AM
\\192.168.13.10\projects\3215\Bridge008\Roadway\XSC\17BP14R68_RDY_XPL.dgn
barross

09/08/99

TIP PROJECT: 17BP.14.R.68

CONTRACT: DN00181



VICINITY MAP

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

MACON COUNTY

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.14.R.68		TS-0

STATE PROJ. NO.	F. A. PROJ. NO.	DESCRIPTION
17BP.14.R.68		PE, R/W, UTIL
17BP.14.R.68		CONST

LOCATION: BRIDGE 008 (OVER ELLIJAY CREEK) ON SR 1001 (ELLIJAY RD.)

TYPE OF WORK: GRADING, PAVING, DRAINAGE & STRUCTURE

STRUCTURE



CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II.

DESIGN DATA

ADT (2008)= 520
ADT (2025)= 1040

V = 35 MPH

FUNC CLASS = LOCAL
SUB-REGIONAL TIER

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT 17BP.14.R.68	=	*0.0944 MI*
LENGTH STRUCTURE TIP PROJECT 17BP.14.R.68	=	*0.006 MI*
TOTAL LENGTH TIP PROJECT 17BP.14.R.68	=	*0.1004 MI*

NCDOT CONTACT: JOSHUA DEYTON, P.E.
PROJECT ENGINEER

Prepared In the Office of:
Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

2012 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE: AUGUST 1, 2013

LETTING DATE: FEBRUARY, 2014

JAMES B. VOSO, P.E.
PROJECT ENGINEER

STEVEN A. CAMPBELL, P.E.
PROJECT DESIGN ENGINEER

BRIDGE ENGINEER

P.E.
SIGNATURE:

DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA

P.E.
STATE HIGHWAY DESIGN ENGINEER

$$$$$$$$SYSTIME$$$$$$
$$$$$$$$$$$$$$$$$$$$DGN$$$$$$$$$$$$$$$$$$$$
$$$$$$USERNAME$$$$$$



SECTION ALONG -L-

APPROXIMATE GROUND LINE ELEVATIONS ARE TAKEN ALONG THE EDGE OF BRIDGE ON UPSTREAM SIDE.

HYDRAULIC DATA

DESIGN DISCHARGE	1100 CFS
FREQUENCY OF DESIGN FLOOD	25 YR.
DESIGN HIGH WATER ELEVATION	2203.70
DRAINAGE AREA	4.25 SQ. MI.
BASE DISCHARGE (Q 100)	1840 CFS
BASE HIGH WATER ELEVATION	2205.75

OVERTOPPING DATA

OVERTOPPING DISCHARGE	1800 CFS
FREQUENCY OF OVERTOPPING FLOOD	200± YR.
OVERTOPPING FLOOD ELEVATION	2207.70

I HEREBY CERTIFY THESE ARE THE AS-BUILT PLANS



PLAN

HORIZONTAL CURVE DATA -L-

PI STA 11+00.00	PI STA 12+25.09	PI STA 14+86.62
△ = 2° 17' 26.2"(RT)	△ = 2° 17' 26.2"(LT)	△ = 35° 10' 18.4"(LT)
D = 2° 17' 30.6"	D = 2° 17' 30.6"	D = 11° 27' 33.0"
L = 99.95'	L = 99.95'	L = 306.93'
T = 49.98'	T = 49.98'	T = 158.47'
R = 2500.00'	R = 2500.00'	R = 500.00'

PROJECT NO. 17BP.14.R.68

MACON COUNTY

STATION: 13+07.80 -L-

SHEET 1 OF 2 REPLACES BRIDGE NO. 008

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

GENERAL DRAWING FOR BRIDGE ON SR 1001 OVER BERRY PRONG ELIJAY CREEK BETWEEN SR 1527 AND SR 1528

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-1
1			3			TOTAL SHEETS
2			4			7

Prepared in the Office of:
Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

NORTH CAROLINA PROFESSIONAL SEAL 14309 ENGINEER STEVEN A. CAMPBELL

DRAWN BY :	PFC	DATE :	06/13
CHECKED BY :	CMT	DATE :	06/13

B.M. #1: RR SPIKE IN 15" BIRCH 35.13' RT. -L- STA. 13+36.07, EL. 2205.51'



LOCATION SKETCH

NO KNOWN UTILITY CONFLICTS.

NOTES:

ASSUMED LIVE LOAD = HL-93 OR ALTERNATE LOADING.

FOR EROSION CONTROL MEASURES, SEE EROSION CONTROL PLANS.

THIS STRUCTURE SHALL BE DESIGNED IN ACCORDANCE WITH THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS.

THIS BRIDGE IS LOCATED IN SEISMIC ZONE 1.

THE EXISTING STRUCTURE CONSISTING OF 1 SPAN AT 20'-6", WITH 24'-7" CLEAR ROADWAY WIDTH, TIMBER FLOOR ON I-BEAMS, ON TIMBER CAPS WITH TIMBER POSTS AND SILLS, AT EXISTING CROSSING FOR PROPOSED STRUCTURE, SHALL BE REMOVED. THE EXISTING BRIDGE IS CURRENTLY POSTED BELOW THE LEGAL LOAD LIMIT. SHOULD THE STRUCTURAL INTEGRITY OF THE BRIDGE FURTHER DETERIORATE, THE LOAD LIMITATION MAY BE REDUCED AS FOUND NECESSARY DURING THE LIFE OF THE PROJECT.

REMOVAL OF THE EXISTING BRIDGE SHALL BE PERFORMED AS NOT TO ALLOW DEBRIS TO FALL INTO THE WATER. THE CONTRACTOR SHALL REMOVE THE BRIDGE AND SUBMIT PLANS FOR DEMOLITION IN ACCORDANCE WITH ARTICLE 402-2 OF THE STANDARD SPECIFICATIONS.

THE MATERIAL SHOWN IN THE CROSS-HATCHED AREA SHALL BE EXCAVATED FOR A DISTANCE OF 30 FT± EACH SIDE OF CENTERLINE ROADWAY AS DIRECTED BY THE ENGINEER. THIS WORK WILL BE PAID FOR AT THE CONTRACT LUMP SUM PRICE FOR UNCLASSIFIED STRUCTURE EXCAVATION. SEE SECTION 412 OF THE STANDARD SPECIFICATIONS.

THE SUBSTRUCTURE OF THE EXISTING BRIDGE INDICATED ON THE PLANS IS FROM THE BEST AVAILABLE INFORMATION. SINCE THIS INFORMATION IS SHOWN FOR THE CONVENIENCE OF THE CONTRACTOR, THE CONTRACTOR SHALL HAVE NO CLAIM WHATSOEVER AGAINST THE DEPARTMENT OF TRANSPORTATION FOR ANY DELAYS OR ADDITIONAL COSTS INCURRED BASED ON DIFFERENCES BETWEEN THE EXISTING BRIDGE SUBSTRUCTURE SHOWN ON THE PLANS AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

THE CONTRACTOR SHALL SUBMIT DESIGN CALCULATIONS AND SHOP DRAWINGS SHOWING COMPLETE DETAILS OF PRECAST CONCRETE CROWNSPAN OR EQUIVALENT, PRECAST CONCRETE WINGWALLS, AND PRECAST CONCRETE HEADWALLS. THE DRAWINGS SHALL INCLUDE PLACING DRAWINGS, REINFORCING STEEL, DETAILS OF RECESSED SEAT, AND ANCHORAGE DETAILS. DRAWINGS AND DESIGN CALCULATIONS, SIGNED AND SEALED BY A PROFESSIONAL ENGINEER REGISTERED IN THE STATE OF NORTH CAROLINA, SHALL BE SUBMITTED BY THE CONTRACTOR FOR REVIEW AND APPROVAL. THE PRICE FOR "PRECAST CONCRETE CROWNSPAN OR EQUIVALENT" SHALL INCLUDE PRECAST WINGWALLS, PRECAST HEADWALLS, INSERTS, ANCHORAGE DEVICES, BEARING PADS/SHIMS, WATERPROOFING, TRANSPORTATION, AND ERECTING FINISHED PRODUCT.

THE MANUFACTURER OF THE PRECAST CONCRETE CROWNSPAN OR EQUIVALENT SHALL PROVIDE LOAD AND RESISTANCE FACTOR RATING (LRFD) SUMMARY PER NCDOT REQUIREMENTS.

FOR LIMITS OF TEMPORARY SHORING FOR MAINTENANCE OF TRAFFIC, SEE TRAFFIC CONTROL PLANS. FOR PAY ITEM FOR TEMPORARY SHORING FOR MAINTENANCE OF TRAFFIC, SEE ROADWAY PLANS.

ASPHALT WEARING SURFACE IS INCLUDED IN ROADWAY QUANTITIES ON ROADWAY PLANS.

THIS STRUCTURE HAS BEEN DESIGNED IN ACCORDANCE WITH "HEC 18-EVALUATING SCOUR AT BRIDGES."

FOR FOUNDATION REQUIREMENTS, SEE SHEETS S-5 AND S-6.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR OTHER DESIGN DATA AND GENERAL NOTES, SEE SHEET SN.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

FOR PRECAST REINFORCED CONCRETE THREE-SIDED CULVERT, SEE SPECIAL PROVISIONS.

INASMUCH AS THE PAINT SYSTEM ON THE EXISTING STRUCTURAL STEEL CONTAINS LEAD, THE CONTRACTOR'S ATTENTION IS DIRECTED TO ARTICLE 107-1 OF THE STANDARD SPECIFICATIONS. ANY COSTS RESULTING FROM COMPLIANCE WITH APPLICABLE STATE OR FEDERAL REGULATIONS PERTAINING TO HANDLING OF MATERIALS CONTAINING LEAD BASED PAINT SHALL BE INCLUDED IN THE BID PRICE FOR "REMOVAL OF EXISTING STRUCTURE AT STATION 13+07.80 -L-."

FOUNDATION NOTES:

THE SPREAD FOOTINGS ARE DESIGNED FOR A FACTORED RESISTANCE OF 6 TSF. CHECK FIELD CONDITIONS FOR THE REQUIRED RESISTANCE OF 14 TSF JUST BEFORE PLACING CONCRETE.

KEY IN SPREAD FOOTINGS AT LEAST 12" INTO ROCK WITH MINIMUM THICKNESS AS SHOWN ON THE PLANS.

TOTAL BILL OF MATERIAL

	REMOVAL OF EXISTING STRUCTURE	UNCLASSIFIED STRUCTURE EXCAVATION	* CLASS A CONCRETE	REINFORCING STEEL	PLAIN RIP RAP CLASS II (2'-0" THICK)	FILTER FABRIC FOR DRAINAGE	30'X30' PRECAST CONCRETE CROWNSPAN OR EQUIVALENT
	LUMP SUM	LUMP SUM	CU. YDS.	LBS.	TONS	SQ. YD.	LUMP SUM
SUPERSTRUCTURE							LUMP SUM
END BENT NO. 1		LUMP SUM	16.1	394	58	63	
END BENT NO. 2		LUMP SUM	6.9	394	52	57	
TOTAL	LUMP SUM	LUMP SUM	23.0	788	110	120	LUMP SUM

* NOTE: THE PAY ITEM "CLASS A CONCRETE" INCLUDES AN APPROXIMATE QUANTITY FOR SUBFOOTING CONCRETE BASED ON THE TOP OF ROCK ELEVATION GIVEN IN THE GEOTECHNICAL REPORT.

PROJECT NO. 17BP.14.R.68

MACON COUNTY

STATION: 13+07.80 -L-

SHEET 2 OF 2 REPLACES BRIDGE NO. 008

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

GENERAL DRAWING
FOR BRIDGE ON
SR 1001 OVER BERRY PRONG
ELIJAY CREEK
BETWEEEN SR 1527 AND SR 1528

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-2
1			3			TOTAL SHEETS
2			4			7

NORTH CAROLINA PROFESSIONAL SEAL 14309 ENGINEER STEVEN A. CAMPBELL

Prepared in the Office of:
Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

DRAWN BY :	PFC	DATE :	03/14
CHECKED BY :	CMT	DATE :	03/14



STAGE 1 CONSTRUCTION

STAGE 1 CONSTRUCTION NOTES:
1. MAINTAIN AN 11'-0" MIN. CLEAR ROADWAY
2. CONTRACTOR SHALL ADD AN ADDITIONAL TIMBER PILE AT END BENT 1 AS TEMPORARY SUPPORT FOR THE PILE CAP AS INDICATED IN THE PLAN VIEW.
3. THE TEMPORARY TRAFFIC BARRIER SHALL BE MOUNTED TO THE TIMBER DECK.
4. DEMOLISH THE 5 MOST UPSTREAM BEAMS AND APPROXIMATELY 10'-5" OF THE DECK.



STAGE 1 TEMPORARY BARRIER

NOTE:
THE 4 - ¾" Ø THROUGH BOLTS WITH WASHERS SHALL CONFORM TO THE REQUIREMENTS OF ASTM A307. BOLTS AND WASHERS SHALL BE GALVANIZED. AT THE CONTRACTOR'S OPTION, STAINLESS STEEL BOLTS AND WASHERS MAY BE USED AS AN ALTERNATE FOR THE ¾" Ø GALVANIZED BOLTS AND WASHERS. THEY SHALL CONFORM TO OR EXCEED THE MECHANICAL REQUIREMENTS OF ASTM A307. THE USE OF THIS ALTERNATE SHALL BE APPROVED BY THE ENGINEER.



STAGE 3 CONSTRUCTION

SECTIONS OF PRECAST CONCRETE CROWNSPAN OR EQUIVALENT SHALL BE CONNECTED PER MANUFACTURER SPECIFICATIONS/RECOMMENDATIONS TO ACT AS ONE UNIT.



STAGE 2 CONSTRUCTION

STAGE 2 CONSTRUCTION NOTES:
1. MAINTAIN A MINIMUM OF 1'-2" BETWEEN THE EXISTING STRUCTURE AND THE NEW STRUCTURE.
2. PROVIDE TEMPORARY SHORING AS NECESSARY DURING STAGING.
3. MAINTAIN AN 11'-0" MIN. CLEAR ROADWAY.
4. DEMOLISH REMAINING PORTION OF EXISTING STRUCTURE.



STAGE 2 TEMPORARY BARRIER

PROJECT NO. 17BP.14.R.68
MACON COUNTY
STATION: 13+07.80 -L-

DRAWN BY :	PFC	DATE :	06/13
CHECKED BY :	CMT	DATE :	06/13

Prepared in the Office of:
Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

NORTH CAROLINA PROFESSIONAL SEAL 14309 ENGINEER STEVEN A. CAMPBELL

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

STAGED CONSTRUCTION FOR BRIDGE 008

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-3
1			3			TOTAL SHEETS
2			4			7



TYPICAL SECTION



SECTION A-A

SECTION B-B

NOTES

THE GUARDRAIL ANCHOR ASSEMBLY FOR CULVERTS SHALL CONSIST OF THE FOLLOWING COMPONENTS :

A. FERRULES SHALL BE MADE FROM STEEL MEETING THE REQUIREMENTS OF AASHTO M169, GRADE 12L14 AND SHALL HAVE A MINIMUM LENGTH OF THREADS OF 2½".

B. 4 - 1" Ø X 2 1/4" BOLTS WITH WASHERS, BOLTS SHALL CONFORM TO THE REQUIREMENTS OF ASTM A307. BOLTS AND WASHERS SHALL BE GALVANIZED. (AT THE CONTRACTOR'S OPTION, STAINLESS STEEL BOLTS AND WASHERS MAY BE USED AS AN ALTERNATE FOR THE 1" Ø X 2 1/4" GALVANIZED BOLTS AND WASHERS. THEY SHALL CONFORM TO OR EXCEED THE MECHANICAL REQUIREMENTS OF ASTM A307. THE USE OF THIS ALTERNATE SHALL BE APPROVED BY THE ENGINEER.)

C. WIRE STRUTS SHOWN IN THE GUARDRAIL ANCHOR ASSEMBLY FOR CULVERTS DETAIL ARE MINIMUM ALLOWABLE SIZE AND SHALL HAVE A MINIMUM TENSILE STRENGTH OF 100,000 P.S.I. AS AN OPTION, A 7/16" Ø WIRE STRUT WITH A MINIMUM TENSILE STRENGTH OF 90,000 PSI IS ACCEPTABLE.

GUARDRAIL ANCHOR ASSEMBLY WITH BOLTS SHALL BE ASSEMBLED IN THE SHOP. BOLT THREADS MAY BE RECUT AS NECESSARY TO INSURE FIT.

THE COST OF THE GUARDRAIL ANCHOR ASSEMBLY FOR CULVERTS COMPLETE IN PLACE, SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR PRECAST CONCRETE CROWNSPAN OR EQUIVALENT.

FERRULES TO BE PLUGGED DURING POURING OF HEADWALLS AS RECOMMENDED BY THE MANUFACTURER.

AT THE PRECASTER'S OPTION, FERRULES WITH OPEN OR CLOSED ENDS MAY BE USED.

PAYMENT FOR GUARDRAIL, POSTS, AND POST BASE PLATES IS INCLUDED IN ROADWAY PAY ITEMS.

SLAB REINFORCING STEEL MAY BE SHIFTED AS NECESSARY TO CLEAR GUARDRAIL ANCHOR ASSEMBLY. CARE SHOULD BE TAKEN TO KEEP THE SHIFTING OF REINFORCING STEEL TO A MINIMUM.

THE CONTRACTOR AND/OR PRECASTER MAY USE ADHESIVELY ANCHORED ANCHOR BOLTS IN PLACE OF GUARDRAIL ANCHOR ASSEMBLY. LEVEL TWO FIELD TESTING IS REQUIRED, AND THE YIELD LOAD OF THE 1"Ø BOLT IS 21.8 KIPS. FOR ADHESIVELY ANCHORED ANCHOR BOLTS OR DOWELS, SEE STANDARD SPECIFICATIONS.



PLAN

SHOWING : GUARDRAIL ANCHOR ASSEMBLY SPACING.



SIDE VIEW



ELEVATION



PLAN

GUARDRAIL ANCHOR ASSEMBLY FOR CULVERTS

PROJECT NO. 17BP.14.R.68

MACON COUNTY

STATION: 13+07.80 -L-

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

ANCHORAGE DETAILS FOR GUARDRAIL ANCHOR ASSEMBLY FOR CULVERTS AND TRANSVERSE SECTION

REVISIONS						SHEET NO. S-4
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			TOTAL SHEETS 7
2			4			

STD. NO. GRA1

ASSEMBLED BY :	PFC	DATE :	06/13
CHECKED BY :	CMT	DATE :	06/13
DRAWN BY : FCJ	6/88	REV. 7/10/01	LES/RDR
CHECKED BY : ARB	6/88	REV. 5/7/03	RWW/JTE
		REV. 5/1/06R	KMM/GM

Prepared in the Office of: Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

NORTH CAROLINA PROFESSIONAL SEAL 14309 ENGINEER STEVEN A. CAMPBELL

$$$$$$SYSTIME$$$$$
$$$$$$$$$$$$$$$$$$$$$$$$$DGN$$$$$$$$$$$$$$$$$$$$$$$$
$$$$USERNAME$$$$



PLAN



NOTE: TOP OF ROCK ELEVATION IS APPROXIMATELY 2194±, SEE NOTES.

ELEVATION

WINGS NOT SHOWN FOR CLARITY.
FOR SECTION A-A, SEE SHEET 3 OF 3.

NOTES

B2 BARS PLACED DURING CONSTRUCTION STAGE 2 SHALL HAVE MECHANICAL COUPLERS CAPABLE OF DEVELOPING 125% OF THE STRENGTH OF THE SPLICED BARS. THE CONTRACTOR SHALL SUBMIT SAMPLES OF HIS PROPOSED SPLICE SYSTEM TO THE ENGINEER FOR REVIEW AND APPROVAL. WELDED SPLICES MAY NOT BE SUBSTITUTED FOR MECHANICAL COUPLERS. THE COST OF MECHANICAL COUPLERS SHALL BE INCLUDED IN THE BID PRICE FOR REINFORCING STEEL. THE CONTRACTOR SHALL COORDINATE BAR LENGTH REQUIREMENTS FOR THE SPLICE SYSTEM USED WITH REINFORCING STEEL.

THE FOOTING SHALL BEAR ON BEDROCK HAVING AN ALLOWABLE BEARING PRESSURE OF 6 TSF OR GREATER. KEY FOOTING A MINIMUM OF 12" INTO ROCK. ADDITION OF UNREINFORCED SUBFOOTING CONCRETE MAY BE REQUIRED TO ACHIEVE THE FOOTING ELEVATIONS SHOWN. IF REQUIRED, SUBFOOTING CONRETE SHALL BE CLASS A AND THE COST SHALL BE INCLUDED IN THE BID ITEM FOR CLASS A CONCRETE. THE FOOTING ELEVATIONS SHOWN ARE BASED ON THE APPROXIMATE ELEVATION OF BEDROCK PROVIDED BY THE GEOTECHNICAL ENGINEER. DUE TO INCONSISTANCIES IN THE BEDROCK, OVER EXCAVATION MAY BE NECESSARY TO ACHIEVE THE REQUIRED FOOTING THICKNESS.



CONSTRUCTION JOINT DETAIL

PROJECT NO. 17BP.14.R.68
MACON COUNTY
STATION: 13+07.80 -L-

SHEET 1 OF 3

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUBSTRUCTURE

FOOTING No. 1

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-5
1			3			TOTAL SHEETS
2			4			7

Prepared in the Office of:
Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

NORTH CAROLINA PROFESSIONAL SEAL 14300 ENGINEER STEVEN A. CAMPBELL

ASSEMBLED BY :	PFC	DATE :	06/13
CHECKED BY :	CMT	DATE :	06/13

$$$$$$SYSTIME$$$$$
$$$$$$$$$$$$$$$$$$$$$$$$$DGN$$$$$$$$$$$$$$$$$$$$$$$
$$$$USERNAME$$$$



PLAN



NOTE: TOP OF ROCK ELEVATION IS APPROXIMATELY 2196±, SEE NOTES.

ELEVATION

WINGS NOT SHOWN FOR CLARITY.
FOR SECTION A-A, SEE SHEET 3 OF 3.

NOTES

B2 BARS PLACED DURING CONSTRUCTION STAGE 2 SHALL HAVE MECHANICAL COUPLERS CAPABLE OF DEVELOPING 125% OF THE STRENGTH OF THE SPLICED BARS. THE CONTRACTOR SHALL SUBMIT SAMPLES OF HIS PROPOSED SPLICE SYSTEM TO THE ENGINEER FOR REVIEW AND APPROVAL. WELDED SPLICES MAY NOT BE SUBSTITUTED FOR MECHANICAL COUPLERS. THE COST OF MECHANICAL COUPLERS SHALL BE INCLUDED IN THE BID PRICE FOR REINFORCING STEEL. THE CONTRACTOR SHALL COORDINATE BAR LENGTH REQUIREMENTS FOR THE SPLICE SYSTEM USED WITH REINFORCING STEEL.

THE FOOTING SHALL BEAR ON BEDROCK HAVING AN ALLOWABLE BEARING PRESSURE OF 6 TSF OR GREATER. KEY FOOTING A MINIMUM OF 12" INTO ROCK. ADDITION OF UNREINFORCED SUBFOOTING CONCRETE MAY BE REQUIRED TO ACHIEVE THE FOOTING ELEVATIONS SHOWN. IF REQUIRED, SUBFOOTING CONRETE SHALL BE CLASS A AND THE COST SHALL BE INCLUDED IN THE BID ITEM FOR CLASS A CONCRETE. THE FOOTING ELEVATIONS SHOWN ARE BASED ON THE APPROXIMATE ELEVATION OF BEDROCK PROVIDED BY THE GEOTECHNICAL ENGINEER. DUE TO INCONSISTANCIES IN THE BEDROCK, OVER EXCAVATION MAY BE NECESSARY TO ACHIEVE THE REQUIRED FOOTING THICKNESS.



CONSTRUCTION JOINT DETAIL

PROJECT NO. 17BP.14.R.68
MACON COUNTY
STATION: 13+07.80 -L-

SHEET 2 OF 3

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUBSTRUCTURE

FOOTING No. 2

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-6
1			3			TOTAL SHEETS
2			4			7

NORTH CAROLINA PROFESSIONAL SEAL 14309 ENGINEER STEVEN A. CAMPBELL
6/14/13

Prepared in the Office of:
Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4562

ASSEMBLED BY :	PFC	DATE :	06/13
CHECKED BY :	CMT	DATE :	06/13

$$$$$$SYSTIME$$$$$
$$$$$$$$$$$$$$$$$$$$$$$$DGN$$$$$$$$$$$$$$$$$$$$$$$$
$$$$USERNAME$$$$



BAGGED STONE AND PIPE SHALL BE PLACED IMMEDIATELY AFTER COMPLETION OF END BENT EXCAVATION. PIPE MAY BE EITHER CONCRETE, CORRUGATED STEEL, CORRUGATED ALUMINUM ALLOY, OR CORRUGATED PLASTIC. PERFORATED PIPE WILL NOT BE ALLOWED.

BAGGED STONE SHALL REMAIN IN PLACE UNTIL THE ENGINEER DIRECTS THAT IT BE REMOVED. THE CONTRACTOR SHALL REMOVE AND DISPOSE OF SILT ACCUMULATIONS AT BAGGED STONE WHEN SO DIRECTED BY THE ENGINEER. BAGS SHALL BE REMOVED AND REPLACED WHENEVER THE ENGINEER DETERMINES THAT THEY HAVE DETERIORATED AND LOST THEIR EFFECTIVENESS.

NO SEPARATE PAYMENT WILL BE MADE FOR THIS WORK AND THE ENTIRE COST OF THIS WORK SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR THE SEVERAL PAY ITEMS.

TEMPORARY DRAINAGE AT END BENT



KEYED FOOTING DETAIL



KEYWAY DETAIL



SECTION A-A

BAR TYPES



ALL BAR DIMENSIONS ARE OUT TO OUT.

BILL OF MATERIAL
FOR ONE END BENT

BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
B1	16	#4	STR	15'-3"	163
S1	32	#4	STR	3'-6"	75
S2	32	#5	1	4'-8"	156

REINFORCING STEEL (FOR ONE END BENT) 394 LBS.

CLASS A CONCRETE BREAKDOWN FOR END BENT NO. 1

POUR #1	SUBFOOTING	9.2 C.Y.
POUR #2	FOOTING	6.9 C.Y.
TOTAL CLASS A CONCRETE FOR END BENT NO. 1		16.1 C.Y.

CLASS A CONCRETE BREAKDOWN FOR END BENT NO. 2

POUR #1	SUBFOOTING	0.0 C.Y.
POUR #2	FOOTING	6.9 C.Y.
TOTAL CLASS A CONCRETE FOR END BENT NO. 1		6.9 C.Y.

PROJECT NO. 17BP.14.R.68

MACON COUNTY

STATION: 13+07.80 -L-

SHEET 3 OF 3

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUBSTRUCTURE

FOOTING No. 1 & 2 DETAILS

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-7
1			3			TOTAL SHEETS
2			4			7

Prepared in the Office of:
Mattern & Craig
CONSULTING ENGINEERS - SURVEYORS
12 BROAD STREET
ASHEVILLE, NORTH CAROLINA 28801
(828) 254-2201 - FAX (828) 254-4962

NORTH CAROLINA PROFESSIONAL ENGINEER SEAL 14309 STEVEN A. CAMPBELL 5/9/13

ASSEMBLED BY : PFC DATE : 06/13
CHECKED BY : CMT DATE : 06/13

$$$$$$$SYSTIME$$$$$
$$$$$$$$$$$$$$$$$$$$$$$$DGN$$$$$$$$$$$$$$$$$$$$$$$$
$$$$USERNAME$$$$$

STANDARD NOTES

DESIGN DATA:

SPECIFICATIONS	A.A.S.H.T.O. (CURRENT)
LIVE LOAD	SEE PLANS
IMPACT ALLOWANCE	SEE A.A.S.H.T.O.
STRESS IN EXTREME FIBER OF	
STRUCTURAL STEEL - AASHTO M270 GRADE 36	20,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50W	27,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50	27,000 LBS. PER SQ. IN.
REINFORCING STEEL IN TENSION	
GRADE 60	24,000 LBS. PER SQ. IN.
CONCRETE IN COMPRESSION	1,200 LBS. PER SQ. IN.
CONCRETE IN SHEAR	SEE A.A.S.H.T.O.
STRUCTURAL TIMBER - TREATED OR	
UNTREATED - EXTREME FIBER STRESS	1,800 LBS. PER SQ. IN.
COMPRESSION PERPENDICULAR TO GRAIN OF TIMBER	375 LBS. PER SQ. IN.
EQUIVALENT FLUID PRESSURE OF EARTH	30 LBS. PER CU. FT. (MINIMUM)

MATERIAL AND WORKMANSHIP:

EXCEPT AS MAY OTHERWISE BE SPECIFIED ON PLANS OR IN THE SPECIAL PROVISIONS, ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE 2012 "STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES" OF THE N. C. DEPARTMENT OF TRANSPORTATION.

STEEL SHEET PILING FOR PERMANENT OR TEMPORARY APPLICATIONS SHALL BE HOT ROLLED.

CONCRETE:

UNLESS OTHERWISE REQUIRED ON PLANS, CLASS A CONCRETE SHALL BE USED FOR ALL PORTIONS OF ALL STRUCTURES WITH THE EXCEPTION THAT: CLASS AA CONCRETE SHALL BE USED IN BRIDGE SUPERSTRUCTURES, ABUTMENT BACKWALLS, AND APPROACH SLABS; AND CLASS B CONCRETE SHALL BE USED FOR SLOPE PROTECTION AND RIP RAP.

CONCRETE CHAMFERS:

UNLESS OTHERWISE NOTED ON THE PLANS, ALL EXPOSED CORNERS ON STRUCTURES SHALL BE CHAMFERED 3/4" WITH THE FOLLOWING EXCEPTIONS: TOP CORNERS OF CURBS MAY BE ROUNDED TO 1-1/2" RADIUS WHICH IS BUILT INTO CURB FORMS; CORNERS OF TRANSVERSE FLOOR EXPANSION JOINTS SHALL BE ROUNDED WITH A 1/4" FINISHING TOOL UNLESS OTHERWISE REQUIRED ON PLANS; AND CORNERS OF EXPANSION JOINTS IN THE ROADWAY FACES AND TOPS OF CURBS AND SIDEWALKS SHALL BE ROUNDED TO A 1/4" RADIUS WITH A FINISHING STONE OR TOOL UNLESS OTHERWISE REQUIRED ON PLANS.

DOWELS:

DOWELS WHEN INDICATED ON PLANS AS FOR CULVERT EXTENSIONS, SHALL BE EMBEDDED AT LEAST 12" INTO THE OLD CONCRETE AND GROUTED INTO PLACE WITH 1:2 CEMENT MORTAR.

ALLOWANCE FOR DEAD LOAD DEFLECTION, SETTLEMENT, ETC. IN CASTING SUPERSTRUCTURES:

BRIDGES SHALL BE BUILT ON THE GRADE OR VERTICAL CURVE SHOWN ON PLANS. SLABS, CURBS AND PARAPETS SHALL CONFORM TO THE GRADE OR CURVE.

ALL DIMENSIONS WHICH ARE GIVEN IN SECTION AND ARE AFFECTED BY DEAD LOAD DEFLECTIONS ARE DIMENSIONS AT CENTER LINE OF BEARING UNLESS OTHERWISE NOTED ON PLANS. IN SETTING FORMS FOR STEEL BEAM BRIDGES AND PRESTRESSED CONCRETE GIRDER BRIDGES, ADJUSTMENTS SHALL BE MADE DUE TO THE DEAD LOAD DEFLECTIONS FOR THE ELEVATIONS SHOWN. WHERE BLOCKS ARE SHOWN OVER BEAMS FOR BUILDING UP TO THE SLAB, THE VERTICAL DIMENSIONS OF THE BLOCKS SHALL BE ADJUSTED BETWEEN BEARINGS TO COMPENSATE FOR DEAD LOAD DEFLECTIONS, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER. WHERE BOTTOM OF SLAB IS IN LINE WITH BOTTOM OF TOP FLANGES, DEPTH OF SLAB BETWEEN BEARINGS SHALL BE ADJUSTED TO COMPENSATE FOR DEAD LOAD DEFLECTION, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER.

IN SETTING FALSEWORK AND FORMS FOR REINFORCED CONCRETE SPANS, AN ALLOWANCE SHALL BE MADE FOR DEAD LOAD DEFLECTIONS, SETTLEMENT OF FALSEWORK, AND PERMANENT CAMBER WHICH SHALL BE PROVIDED FOR IN ADDITION TO THE ELEVATIONS SHOWN. AFTER REMOVAL OF THE FALSEWORK, THE FINISHED STRUCTURES SHALL CONFORM TO THE PROFILE AND ELEVATIONS SHOWN ON THE PLANS AND CONSTRUCTION ELEVATIONS FURNISHED BY THE ENGINEER.

DETAILED DRAWINGS FOR FALSEWORK OR FORMS FOR BRIDGE SUPERSTRUCTURE AND ANY STRUCTURE OR PARTS OF A STRUCTURE AS NOTED ON THE PLANS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE CONSTRUCTION OF THE FALSEWORK OR FORMS IS STARTED.

REINFORCING STEEL:

ALL REINFORCING STEEL SHALL BE DEFORMED. DIMENSIONS RELATIVE TO PLACEMENT OF REINFORCING ARE TO CENTERS OF BARS UNLESS OTHERWISE INDICATED IN THE PLANS. DIMENSIONS ON BAR DETAILS ARE TO CENTERS OF BARS OR ARE OUT TO OUT AS INDICATED ON PLANS.

WIRE BAR SUPPORTS SHALL BE PROVIDED FOR REINFORCING STEEL WHERE INDICATED ON THE PLANS. WHEN BAR SUPPORT PIECES ARE PLACED IN CONTINUOUS LINES, THEY SHALL BE SO PLACED THAT THE ENDS OF THE SUPPORTING WIRES SHALL BE LAPPED TO LOCK LEGS ON ADJOINING PIECES.

STRUCTURAL STEEL:

AT THE CONTRACTOR'S OPTION, HE MAY SUBSTITUTE 7/8" Ø SHEAR STUDS FOR THE 3/4" Ø STUDS SPECIFIED ON THE PLANS. THIS SUBSTITUTION SHALL BE MADE AT THE RATE OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS, AND STUD SPACING CHANGES SHALL BE MADE AS NECESSARY TO PROVIDE THE SAME EQUIVALENT NUMBER OF 7/8" Ø STUDS ALONG THE BEAM AS SHOWN FOR 3/4" Ø STUDS BASED ON THE RATIO OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS. STUDS OF THE LENGTH SPECIFIED ON THE PLANS MUST BE PROVIDED. THE MAXIMUM SPACING SHALL BE 2'-0".

EXCEPT AT THE INTERIOR SUPPORTS OF CONTINUOUS BEAMS WHERE THE COVER PLATE IS IN CONTACT WITH BEARING PLATE, THE CONTRACTOR MAY, AT HIS OPTION, SUBSTITUTE FOR THE COVER PLATES DESIGNATED ON THE PLANS COVER PLATES OF THE EQUIVALENT AREA PROVIDED THESE PLATES ARE AT LEAST 5/16" IN THICKNESS AND DO NOT EXCEED A WIDTH EQUAL TO THE FLANGE WIDTH LESS 2" OR A THICKNESS EQUAL TO 2 TIMES THE FLANGE THICKNESS. THE SIZE OF FILLET WELDS SHALL CONFORM TO THE REQUIREMENTS OF THE CURRENT ANSI/AASHTO/AWS "BRIDGE WELDING CODE". ELECTROSLAG WELDING WILL NOT BE PERMITTED.

WITH THE SOLE EXCEPTION OF EDGES AT SURFACES WHICH BEAR ON OTHER SURFACES, ALL SHARP EDGES AND ENDS OF SHAPES AND PLATES SHALL BE SLIGHTLY ROUNDED BY SUITABLE MEANS TO A RADIUS OF APPROXIMATELY 1/16 INCH OR EQUIVALENT FLAT SURFACE AT A SUITABLE ANGLE PRIOR TO PAINTING, GALVANIZING, OR METALLIZING.

HANDRAILS AND POSTS:

METAL STANDARDS AND FACES OF THE CONCRETE END POSTS FOR THE METAL RAIL SHALL BE SET NORMAL TO THE GRADE OF THE CURB, UNLESS OTHERWISE SHOWN ON PLANS. THE METAL RAIL AND TOPS OF CONCRETE POSTS USED WITH THE ALUMINUM RAIL SHALL BE BUILT PARALLEL TO THE GRADE OF THE CURB.

METAL HANDRAILS SHALL BE IN ACCORDANCE WITH THE PLANS. RAILS SHALL BE AS MANUFACTURED FOR BRIDGE RAILING. CASTINGS SHALL BE OF A UNIFORM APPEARANCE. FINS AND OTHER DEFORMATIONS RESULTING FROM CASTING OR OTHERWISE SHALL BE REMOVED IN A MANNER SO THAT A UNIFORM COLORING OF THE COMPLETED CASTING SHALL BE OBTAINED. CASTINGS WITH DISCOLORATIONS OR OF NON-UNIFORM COLORING WILL NOT BE ACCEPTED. CERTIFIED MILL REPORTS ARE REQUIRED FOR METAL RAILS AND POSTS.

SPECIAL NOTES:

GENERALLY, IN CASE OF DISCREPANCY, THIS STANDARD SHEET OF NOTES SHALL GOVERN OVER THE SPECIFICATIONS, BUT THE REMAINDER OF THE PLANS SHALL GOVERN OVER NOTES HEREON, AND SPECIAL PROVISIONS SHALL GOVERN OVER ALL. SEE SPECIFICATIONS ARTICLE 105-4.

ENGLISH

JANUARY, 1990

STD. NO. SN

REV. 6-16-95 EEM (W) RGW REV. 5-7-03 RWW (W) JTE REV. 10-1-11 MAA (W) GM
REV. 8-16-99 RWW (W) LES REV. 5-1-06 TLA (W) GM

$$$$$$SYSTIME$$$$$
$$$$$$$$$$$$$$$$$$$$$$DGN$$$$$$$$$$$$$$$$$$$$$$$$
$$$$USERNAME$$$$